



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey ESA Pneumatic Professional Series L-Sealers



At a Glance

- Pneumatic cylinder
- Cast seal head available with hot knife seal systems
- Adjustable product tray easily separates film and accommodates variety of product sizes
- Adjustable pin perforator provides air evacuation in film
- Heavy-duty film cradle allows for quick and easy adjustment and changeover
- Simple, easy-to-use control panel with automatic cycle timing
- Dual locking magnet clamps apply consistent pressure across seal bar
- Takeaway conveyor can be raised or lowered to center the seal on your product
- All-welded main frame from quarter-inch cold rolled steel
- Heavy-duty industrial design and construction for trouble-free service and long life
- Made in the USA

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Pneumatic Operation for Faster Shrink Packaging

Eastey ESA Professional Series L-Sealers have cast seal arms with pneumatic operation for even faster shrink packaging on your most demanding packaging and production lines.

Eastey ESA Professional Series Pneumatic L-Sealers provide top of the line features and the most robust L-Sealer design on the market today. Expertly welded from 0.25" cold rolled steel, Eastey Professional L-Sealers reliably perform in the most demanding real-world shrink wrap production requirements. As a measure of strength, Eastey L-Sealers weigh nearly twice as much as competitive models.

Eastey has been a leader in the shrink packaging industry for over 25 years. Eastey L-Sealers are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC. Cast seal arms, stainless steel film clamps, and heavy-duty dual magnet clamping are just some of the features that provide the durability you need.

Models

ESA2016TK, ESA2028TK, ESA2040TK, ESA2050TK, ESA2070TK, ESA2080TK, ESA20100TK

ESA3040TK, ESA3050TK, ESA3070TK, ESA3080TK, ESA30100TK

ESA4040TK, ESA4050TK, ESA4070TK, ESA4080TK, ESA40100TK

ESA5050TK, ESA5070TK, ESA5080TK, ESA50100TK

Standard Features

Designed to seal most polyolefin, polyethylene, and PVC shrink films
All-welded main frame from cold rolled steel
Built-in drawer for tools or spare parts
Seal head casting equipped with head return cylinder
Stainless steel film clamps hold film in place while sealing
Dual palm pneumatic seal head activation
Hot knife seal systems available with mushroom (standard), pancake, or arrow inserts
Dual locking magnet clamps apply even pressure across sealbar
Adjustable dwell time for better seal control
Solid state temperature control adjustable for a variety of films
Adjustable product tray accommodates wide variety of product sizes
Takeaway conveyor can be raised or lowered to center-seal product
Automatic takeaway conveyor
Heavy-duty film cradle allows for easy changeovers and adjustments
Adjustable pin perforator provides air evacuation
Side seal size from 20" to 50", front seal size from 16" to 100"
Maximum film width up to 44"
Maximum film roll OD up to 12", 10" with power unwind
Custom two-part epoxy finish resists scratching
Heavy-duty casters for transportation within plant
Available in 110v, 220v, or optional 480v
60-80 psi air requirement
Easy-to-use design requires minimal training and maintenance
Made in the USA

Optional Accessories

Power film unwind allows free feeding of film increasing operator efficiency
Film inverting head increases production by bringing film off the back of machine, opening the film, and minimizing operator effort
Hot knife inserts available mushroom, pancake, poly, or arrow styles
Left hand models available
DuoSeal continuously heated seal bar
Lower conveyor
Product guides and / or product tray

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the Eastey Professional Series

Model	Seal Dimensions		Machines Dimensions			Standard Power			Weight	Ship Wt.
	Front	Side	Width	Height	Length	Volts	Amps	Phase		
ESA2016TK	16" (41cm)	20" (51cm)	34" (86cm)	44" (112cm)	63" (160cm)	220/110	10/20	1	600 lbs (272 kg)	700 lbs (317 kg)
ESA2028T(K)	28" (71cm)	20" (51cm)	34" (86cm)	44" (112cm)	84" (213cm)	220/110	10/20	1	700 lbs (317 kg)	800 lbs (362 kg)
ESA2040T(K)	40" (102cm)	20" (51cm)	34" (86cm)	44" (112cm)	106" (269cm)	220	15	1	800 lbs (362 kg)	900 lbs (408 kg)
ESA2050TK	50" (127cm)	20" (51cm)	34" (86cm)	44" (112cm)	126" (320cm)	220	20	1	900 lbs (408 kg)	1000 lbs (453 kg)
ESA2070TK	70" (178cm)	20" (51cm)	34" (86cm)	44" (112cm)	167" (424cm)	220	25	1	1300 lbs (589 kg)	1400 lbs (635 kg)
ESA2080TK	80" (203cm)	20" (51cm)	34" (86cm)	44" (112cm)	187" (474cm)	220	20	1	1500 lbs (680 kg)	1600 lbs (725 kg)
ESA20100TK	100" (203cm)	20" (51cm)	34" (86cm)	44" (112cm)	227" (577cm)	220	20	1	1900 lbs (861 kg)	2000 lbs (907 kg)
ESA3040TK	40" (102cm)	30" (76cm)	43" (109cm)	44" (112cm)	106" (269cm)	220	20	1	1200 lbs (544 kg)	1300 lbs (591 kg)
ESA3050TK	50" (127cm)	30" (76cm)	43" (109cm)	44" (112cm)	126" (320cm)	220	20	1	1300 lbs (591 kg)	1400 lbs (637 kg)
EM3070TK	70" (177cm)	30" (76cm)	43" (109cm)	44" (112cm)	167" (424cm)	220	25	1	1600 lbs (728 kg)	1700 lbs (774 kg)
ESA3080TK	80" (203cm)	30" (76cm)	43" (109cm)	44" (112cm)	187" (474cm)	220	25	1	1800 lbs (819 kg)	1900 lbs (861 kg)
ESA30100TK	100" (254cm)	30" (76cm)	43" (109cm)	44" (112cm)	227" (577cm)	220	25	1	2100 lbs (956 kg)	2200 lbs (997 kg)
ESA4040TK*	40" (101cm)	40" (101cm)	53" (135cm)	44" (112cm)	106" (269cm)	220	20	1	1700 lbs (774 kg)	1800 lbs (819 kg)

ESA4050TK*	50" (127cm)	40" (101cm)	53" (135cm)	44" (112cm)	126" (320cm)	220	20	1	1900 lbs (861 kg)	2000 lbs (907 kg)
ESA4070TK*	70" (177cm)	40" (101cm)	53" (135cm)	44" (112cm)	167" (424cm)	220	25	1	2100 lbs (956 kg)	2200 lbs (997 kg)
ESA4080TK*	80" (203cm)	40" (101cm)	53" (135cm)	44" (112cm)	187" (474cm)	220	25	1	2300 lbs (1043 kg)	2400 lbs (1092 kg)
ESA40100TK*	100" (254cm)	40" (101cm)	53" (135cm)	44" (112cm)	227" (577cm)	220	25	1	2600 lbs (1179 kg)	2700 lbs (1229 kg)
ESA5050TK*	50" (127cm)	50" (127cm)	63" (160cm)	44" (112cm)	126" (320cm)	220	20	1	1900 lbs (861 kg)	2000 lbs (907 kg)
ESA5070TK*	70" (177cm)	50" (127cm)	63" (160cm)	44" (112cm)	167" (424cm)	220	25	1	2100 lbs (956 kg)	2200 lbs (997 kg)
ESA5080TK*	80" (203cm)	50" (127cm)	63" (160cm)	44" (112cm)	187" (474cm)	220	25	1	2300 lbs (1043 kg)	2400 lbs (1092 kg)
ESA50100TK*	100" (254cm)	50" (127cm)	63" (160cm)	44" (112cm)	227" (577cm)	220	25	1	2600 lbs (1179 kg)	2700 lbs (1229 kg)

*Powered film unwind included