



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Eastey Professional Series L-Sealers



## At a Glance

- Cast seal head available in hot knife or hot wire seal systems
- Adjustable product tray easily separates film and accommodates variety of product sizes
- Adjustable pin perforator provides air evacuation in film
- Heavy-duty film cradle allows for quick and easy adjustment and changeover
- Simple, easy-to-use control panel with automatic cycle timing
- Dual locking magnet clamps apply consistent pressure across seal bar
- Takeaway conveyor can be raised or lowered to center the seal on your product
- All-welded main frame from quarter-inch cold rolled steel
- Heavy-duty industrial design and construction for trouble-free service and long life
- Made in the USA

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Work Horse Semi-Auto L-Sealers with Premium Features

Eastey Professional Series L-Sealers have several options for you to customize the ultimate workhorse for your shrink packaging requirements.

Eastey Professional Series L-Sealers provide top of the line features and the most robust L-Sealer design on the market today. Expertly welded from 0.25" cold rolled steel, Eastey Professional L-Sealers reliably perform in the most demanding real-world shrink wrap production requirements. As a measure of strength, Eastey L-Sealers weigh nearly twice as much as competitive models.

Eastey has been a leader in the shrink packaging industry for over 25 years. Eastey L-Sealers are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC. Cast seal arms, stainless steel film clamps, and heavy-duty dual magnet clamping are just some of the features that provide the durability you need.

# Models

EM2016T(K), EM2028T(K), EM2040T(K), EM2050T(K), EM2070TK, EM2080TK, EM20100TK

EM3040T(K), EM3050T(K), EM3070TK, EM3080TK, EM30100TK

EM4040T(K), EM4050T(K), EM4070TK, EM4080TK, EM40100TK

EM5050TK, EM5070TK, EM5080TK, EM50100TK

## Standard Features

Designed to seal most polyolefin, polyethylene, and PVC shrink films

All-welded main frame from 0.25" cold rolled steel

Built-in drawer for tools or spare parts

Seal head casting equipped with head return cylinder

Stainless steel film clamps hold film in place while sealing

Available with hot wire or hot knife seal systems

Hot knife seal systems available with mushroom (standard), pancake, arrow, or poly inserts

Dual locking magnet clamps apply even pressure across sealbar

Adjustable dwell time for better seal control

Solid state temperature control adjustable for a variety of films

Adjustable product tray accommodates wide variety of product sizes

Takeaway conveyor can be raised or lowered to center-seal product

Automatic takeaway conveyor

Heavy-duty film cradle allows for easy changeovers and adjustments

Adjustable pin perforator provides air evacuation

Side seal size from 20" to 50", front seal size from 16" to 100"

Maximum film width up to 44"

Maximum film roll OD up to 12", 10" with power unwind

Custom two-part epoxy finish resists scratching

Heavy-duty casters for transportation within plant

Available in 110v, 220v, or optional 480v

Easy-to-use design requires minimal training and maintenance

Made in the USA

## Optional Accessories

Power film unwind allows free feeding of film increasing operator efficiency

Film inverting head increases production by bringing film off the back of machine, opening the film, and minimizing operator effort

Hot knife inserts available mushroom, pancake, poly, or arrow styles

Stainless steel and left hand models available

DuoSeal continuously heated seal bar

Lower conveyor

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

# Specifications of the Easte Professional Series

| Model       | Seal Dimensions |                | Machines Dimensions |                |                 | Standard Power |       |       | Weight               | Ship Wt.             |
|-------------|-----------------|----------------|---------------------|----------------|-----------------|----------------|-------|-------|----------------------|----------------------|
|             | Front           | Side           | Width               | Height         | Length          | Volts          | Amps  | Phase |                      |                      |
| EM2016T(K)  | 16"<br>(41cm)   | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 63"<br>(160cm)  | 220/110        | 10/20 | 1     | 600 lbs<br>(272 kg)  | 700 lbs<br>(317 kg)  |
| EM2028T(K)  | 28"<br>(71cm)   | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 84"<br>(213cm)  | 220/110        | 10/20 | 1     | 700 lbs<br>(317 kg)  | 800 lbs<br>(362 kg)  |
| EM2040T(K)  | 40"<br>(102cm)  | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 106"<br>(269cm) | 220            | 15    | 1     | 800 lbs<br>(362 kg)  | 900 lbs<br>(408 kg)  |
| EM2050T(K)  | 50"<br>(127cm)  | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 126"<br>(320cm) | 220            | 20    | 1     | 900 lbs<br>(408 kg)  | 1000 lbs<br>(453 kg) |
| EM2070TK    | 70"<br>(178cm)  | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 167"<br>(424cm) | 220            | 25    | 1     | 1300 lbs<br>(589 kg) | 1400 lbs<br>(635 kg) |
| EM2080TK    | 80"<br>(203cm)  | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 187"<br>(474cm) | 220            | 20    | 1     | 1500 lbs<br>(680 kg) | 1600 lbs<br>(725 kg) |
| EM20100TK   | 100"<br>(203cm) | 20"<br>(51cm)  | 34"<br>(86cm)       | 44"<br>(112cm) | 227"<br>(577cm) | 220            | 20    | 1     | 1900 lbs<br>(861 kg) | 2000 lbs<br>(907 kg) |
| EM3040T(K)  | 40"<br>(102cm)  | 30"<br>(76cm)  | 43"<br>(109cm)      | 44"<br>(112cm) | 106"<br>(269cm) | 220            | 20    | 1     | 1200 lbs<br>(544 kg) | 1300 lbs<br>(591 kg) |
| EM3050T(K)  | 50"<br>(127cm)  | 30"<br>(76cm)  | 43"<br>(109cm)      | 44"<br>(112cm) | 126"<br>(320cm) | 220            | 20    | 1     | 1300 lbs<br>(591 kg) | 1400 lbs<br>(637 kg) |
| EM3070TK    | 70"<br>(177cm)  | 30"<br>(76cm)  | 43"<br>(109cm)      | 44"<br>(112cm) | 167"<br>(424cm) | 220            | 25    | 1     | 1600 lbs<br>(728 kg) | 1700 lbs<br>(774 kg) |
| EM3080TK    | 80"<br>(203cm)  | 30"<br>(76cm)  | 43"<br>(109cm)      | 44"<br>(112cm) | 187"<br>(474cm) | 220            | 25    | 1     | 1800 lbs<br>(819 kg) | 1900 lbs<br>(861 kg) |
| EM30100TK   | 100"<br>(254cm) | 30"<br>(76cm)  | 43"<br>(109cm)      | 44"<br>(112cm) | 227"<br>(577cm) | 220            | 25    | 1     | 2100 lbs<br>(956 kg) | 2200 lbs<br>(997 kg) |
| EM4040T(K)* | 40"<br>(101cm)  | 40"<br>(101cm) | 53"<br>(135cm)      | 44"<br>(112cm) | 106"<br>(269cm) | 220            | 20    | 1     | 1700 lbs<br>(774 kg) | 1800 lbs<br>(819 kg) |

|             |                 |                |                |                |                 |     |    |   |                       |                       |
|-------------|-----------------|----------------|----------------|----------------|-----------------|-----|----|---|-----------------------|-----------------------|
| EM4050T(K)* | 50"<br>(127cm)  | 40"<br>(101cm) | 53"<br>(135cm) | 44"<br>(112cm) | 126"<br>(320cm) | 220 | 20 | 1 | 1900 lbs<br>(861 kg)  | 2000 lbs<br>(907 kg)  |
| EM4070TK*   | 70"<br>(177cm)  | 40"<br>(101cm) | 53"<br>(135cm) | 44"<br>(112cm) | 167"<br>(424cm) | 220 | 25 | 1 | 2100 lbs<br>(956 kg)  | 2200 lbs<br>(997 kg)  |
| EM4080TK*   | 80"<br>(203cm)  | 40"<br>(101cm) | 53"<br>(135cm) | 44"<br>(112cm) | 187"<br>(474cm) | 220 | 25 | 1 | 2300 lbs<br>(1043 kg) | 2400 lbs<br>(1092 kg) |
| EM40100TK*  | 100"<br>(254cm) | 40"<br>(101cm) | 53"<br>(135cm) | 44"<br>(112cm) | 227"<br>(577cm) | 220 | 25 | 1 | 2600 lbs<br>(1179 kg) | 2700 lbs<br>(1229 kg) |
| EM5050TK*   | 50"<br>(127cm)  | 50"<br>(127cm) | 63"<br>(160cm) | 44"<br>(112cm) | 126"<br>(320cm) | 220 | 20 | 1 | 1900 lbs<br>(861 kg)  | 2000 lbs<br>(907 kg)  |
| EM5070TK*   | 70"<br>(177cm)  | 50"<br>(127cm) | 63"<br>(160cm) | 44"<br>(112cm) | 167"<br>(424cm) | 220 | 25 | 1 | 2100 lbs<br>(956 kg)  | 2200 lbs<br>(997 kg)  |
| EM5080TK*   | 80"<br>(203cm)  | 50"<br>(127cm) | 63"<br>(160cm) | 44"<br>(112cm) | 187"<br>(474cm) | 220 | 25 | 1 | 2300 lbs<br>(1043 kg) | 2400 lbs<br>(1092 kg) |
| EM50100TK*  | 100"<br>(254cm) | 50"<br>(127cm) | 63"<br>(160cm) | 44"<br>(112cm) | 227"<br>(577cm) | 220 | 25 | 1 | 2600 lbs<br>(1179 kg) | 2700 lbs<br>(1229 kg) |

\*Powered film unwind included