



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey VSA1825 Value Series Automatic L-Sealer



At a Glance

- 18 inch x 25 inch seal area for packages up to 7 inches tall
- User interface simple menus for easy operation
- High-speed product indexing
- Seal head pneumatic air cylinder for automatic sealing
- Motorized seal height adjustment for various product sizes
- All-welded main frame from 12 gauge steel

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Reliable Automatic L-Sealer with 18" x 25" Seal Area

Eastey VSA1825 Auto L-Sealer handles day-to-day operation required for automatic sealing and provides all the quality features found in much higher priced machines. These L-sealers are designed and built to give performance needed for positive sealing a wide variety of polyolefin shrink films.

The Eastey VSA1825 is designed specifically for automatic L-sealing applications that require simple operation and a small footprint.

Products are automatically fed into the VSA1825 where a product sensor detects the product as it moves into the sealing area. Once in position, a 90° guillotine hot knife seal bar automatically seals the film edges to create a loose bag around the product. Once sealed, the product transfers to a heat tunnel to shrink the film and provide a clean, finished product.

The efficient automatic seal system allows users to seal between 35 – 40 products per minute, depending on product size and application requirements.

Standard Features

- Designed to seal polyolefin shrink films
- All-welded main frame from 12 gauge steel
- Normal speed infeed and outfeed conveyors
- High speed with product indexing
- Motorized seal height adjustment for various product sizes

Seal head equipped with pneumatic air cylinder for automatic sealing
 Designed to seal most center-folded polyolefin and polyethylene shrink films
 Adjustable pin perforators provide air evacuation
 Infeed and outfeed conveyors run at 100 f/min (30.5 m/min)
 Motorized seal height adjustment to center seal line for various product sizes
 Seal head equipped with pneumatic air cylinder for automatic sealing
 PTFE hot knife seal bar with vertical cutting motion for consistent and clean seal
 Consistent pressure across seal bar
 Automatic cycle timing with adjustable dwell time
 7" color touchscreen controller for user interface and system setup
 Film tracking wheels keep film in place; scrap film take-up wheel included
 Heavy duty casters and leveling pads for transportation within plant
 Easy to use design requires minimal training and maintenance
 18"W x 25"L seal area for packages up to 7" tall
 Maximum film width up to 24"
 Maximum film roll OD up to 12"
 60 – 80 PSI, 0.25" NPT fitting
 CE Certification

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the Eastey VSA1825

Model	Machines Dimensions			Product Size			Film	Electrical	Ship Wt
	Width	Height	Length	Length	Width	Height	Width		
VSA1825	57.1" (1450mm)	66.2" (1680mm)	75.2" (1910mm)	2.5" - 22.0" (64mm - 559mm)	2.5" - 16.0" (64mm - 406mm)	0.2" - 7.0" (5mm - 178mm)	24" (610mm)	220V, 12A, 1Ph	1490 lbs (676 kg)