



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey Performance Series Shrink Heat Tunnels



At a Glance

- Stainless steel mesh belt conveyor provides maintenance-free operation
- Live roller conveyor provides a more finished look for retail packaging applications
- Easy-to-use control panel lets operators adjust for the specific needs of the application
- Air flow knob gives variable air flow adjustments at your fingertips
- Inside the tunnel, four directional air flow provides positive shrinking
- Positive shrinking on most polyolefin, polyethylene, and PVC films
- Heavy-duty industrial design and construction for trouble-free service and long life
- Made in the USA

Buy your [shrink film](#) from us, and get a discount on this Eastey shrink tunnel!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Reliable, Durable Shrink Tunnels

Eastey Performance Series Shrink Tunnels offer the reliability needed to provide positive shrinking of a wide range of films at a cost-effective price.

Proven reliable, these intermediate level Eastey Shrink Tunnels provide you with all the quality features found in much higher priced machines. These heat tunnels are designed and built to give you all the performance features needed for positive shrinking a wide variety of films including polyolefin, polyethylene, and PVC.

Eastey Performance Series Shrink Tunnels are expertly welded on 12 gauge steel frames and designed to produce superior shrinking on a virtually any package. Variable four-direction air flow, variable air velocity and delayed cool down are just some of the features that provide the durability you need.

Models

ET1608-30, ET1610-36, ET1610-48, ET2010-36

Standard Features

Designed to seal most polyolefin, polyethylene, and PVC shrink films

All-welded main frame from 12 gauge steel

Live roller or stainless steel mesh belt conveyors; optional dead roller conveyor for polyethylene

Sealed bearings (not bushings) on drive and idler shafts

Adjustable digital solid state temperature control for a variety of films
 Four-directional air flow provides positive shrinking
 Variable air flow and air velocity for a variety of products and applications
 Bottom air flow adjustment; full on, half on, full off on ET2010
 Large ducting creates more air volume inside tunnel
 Optional top and side plates for air flow patterning and quick changeover for different products on ET2010
 Plugs available for patterned air flow
 Delayed cool down and over temperature protection
 Fold down electrical control panel for easy maintenance
 Conveyor speed up to 67 feet per minute
 Heavy-duty casters for transportation within plant
 Leveling legs provide sturdy base once in place
 Custom two part epoxy finish resists scratching
 Available in 220v, single or 3-phase
 Easy-to-use design requires minimal training, maintenance, and trouble free operation
 Made in the USA

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the Eastey Performance Series Shrink Tunnels

Model	Machine Dimensions			Chamber Dimensions			Conveyor Dimensions		Standard Power			Weight	Ship Wt.
	Width	Height	Length	Width	Height	Length	Width	Length	Volts	Amps	Phase		
ET1608-30	29" (74cm)	49" (124cm)	40" (101cm)	16" (41cm)	8" (20cm)	30" (76cm)	16" (41cm)	40" (102cm)	220	40/25	1/3	650 lbs (294 kg)	750 lbs (340 kg)
ET1610-36	28" (72cm)	64" (163cm)	49" (125cm)	16" (41cm)	10" (25cm)	36" (91cm)	16" (41cm)	48" (122cm)	220	40/25	1/3	650 lbs (294 kg)	750 lbs (340 kg)
ET1610-48	28" (72cm)	64" (163cm)	61" (155cm)	16" (41cm)	10" (25cm)	48" (122cm)	16" (41cm)	60" (152cm)	220	40/25	1/3	750 lbs (294 kg)	850 lbs (386 kg)
ET2010-36	38" (97cm)	51" (129cm)	49" (124cm)	20" (51cm)	10" (25cm)	36" (91cm)	20" (51cm)	49" (124cm)	220	40/25	1/3	700 lbs (317 kg)	800 lbs (364 kg)