



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey Professional Series Shrink Heat Tunnels



At a Glance

- Stainless steel mesh belt conveyor provides maintenance-free operation
- Live roller conveyor provides a more finished look for retail packaging applications
- Easy to use control panel lets operators adjust for the specific needs of the application
- Air flow knob gives variable air flow adjustments at your fingertips
- Inside the tunnel, four directional air flow provides positive shrinking
- Positive shrinking on most polyolefin, polyethylene, and PVC films
- Heavy-duty industrial design and construction for trouble-free service and long life
- Made in the USA

Buy your [shrink film](#) from us, and get a discount on this Eastey shrink tunnel!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Work Horse Shrink Tunnels with Premium Features

Eastey Professional Series Shrink Tunnels are the ultimate workhorse for your most demanding shrink wrapping requirements.

Eastey Professional Series Shrink Tunnels provide top of the line features and the most robust design on the market today. Expertly welded from 0.25" cold rolled steel, Eastey Professional Shrink Tunnels reliably perform in the most demanding real-world shrink wrap production requirements. As a measure of strength, Eastey L-Sealers weigh nearly twice as much as competitive models.

Eastey has been a leader in the shrink packaging industry for over 25 years. Eastey L-Sealers are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC. Variable four-direction air flow, variable air velocity and delayed cool down are just some of the features that provide the durability you need.

Models

ET2008, ET2012, ET2016, ET2020

ET2408, ET2412, ET2416, ET2420

ET3608, ET3612, ET3616, ET3620

ET4808, ET4812, ET4816, ET4820

ET5608, ET5612, ET5616, ET5620

ET7008, ET7012, ET7016, ET7020

Standard Features

Designed to seal most polyolefin, polyethylene, and PVC shrink films
All-welded main frame from 12 gauge cold rolled steel
Live roller, dead roller, or stainless steel mesh belt conveyor standard; optional plastic belt conveyor
Sealed bearings (not bushings) on drive and idler shafts
Adjustable digital solid state temperature control for a variety of films
Four-directional air flow provides positive shrinking
Variable air flow for a variety of products and applications
Large ducting creates more air volume inside tunnel
Plugs available for patterned air flow
Optional top and side plates for air flow patterning and quick changeover for different products
Delayed cool down and over temperature protection
Fold down electrical control panel for easy maintenance
Live roller conveyor speed up to 67 fpm, mesh belt conveyor speed up to 100 fpm
Heavy-duty casters for transportation within plant
Leveling legs provide sturdy base once in place
Custom two part epoxy finish resists scratching
Stainless steel models available on ET20
220v 3-phase standard, some models available in 220v single-phase or 480v 3-phase
Easy-to-use design requires minimal training, maintenance, and trouble free operation
Made in the USA

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the Easte Professional Series Shrink Tunnels

Model	Machine Dimensions			Chamber Dimensions			Conveyor Dimensions		Standard Power			Weight	Ship Wt.
	Width	Height	Length	Width	Height	Length	Width	Length	Volts	Amps	Phase		
ET20	33" (84cm)	56"- 72" (142- 183cm)	74" (188cm)	20" (51cm)	4"-20" (10- 51cm)	52" (132cm)	20" (51cm)	72" (183cm)	220	50	3	900 lbs (410 kg)	1200 lbs (546 kg)
ET24	37" (94cm)	56"- 72" (142- 183cm)	74" (188cm)	24" (51cm)	4"-20" (10- 51cm)	52" (132cm)	24" (61cm)	72" (183cm)	220	50	3	1000 lbs (455 kg)	1250 lbs (569 kg)
ET36	49" (124cm)	56"- 72" (142- 183cm)	74" (188cm)	36" (91cm)	4"-20" (10- 51cm)	52" (132cm)	36" (91cm)	72" (183cm)	220	50-60	3	1300 lbs (591 kg)	1600 lbs (728 kg)
ET48	61" (155cm)	56"- 72" (142- 183cm)	74" (188cm)	48" (122cm)	4"-20" (10- 51cm)	52" (132cm)	48" (122cm)	72" (183cm)	220	80- 90- 100	3	1700 lbs (773 kg)	2000 lbs (910 kg)
ET56	69" (124cm)	56"- 72" (142- 183cm)	74" (188cm)	56" (142cm)	4"-20" (10- 51cm)	52" (132cm)	56" (142cm)	72" (183cm)	220	90- 110	3	2000 lbs (910 kg)	2300 lbs (1047 kg)
ET70	83" (211cm)	56"- 72" (142- 183cm)	74" (188cm)	70" (179cm)	4"-20" (10- 51cm)	52" (132cm)	70" (179cm)	72" (183cm)	220	90- 110	3	2500 lbs (1138 kg)	2800 lbs (1274 kg)