



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey VST1710 Value Series Shrink Tunnel



At a Glance

- Live roller conveyor with silicone coated rollers provides a smooth finish
- Conveyor speed up to 100 feet per minute
- High velocity blower motors
- Positive shrinking on most polyolefin, polyethylene, and PVC films
- Heavy-duty industrial design and construction for trouble-free service and long life

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

High Quality Lower Cost Shrink Tunnel

Eastey Value Series Shrink Tunnels provide all the quality features found in much higher priced machines. These shrink tunnels are designed and built to give you all the performance features needed for positive shrinking of polyolefin shrink films and match up perfectly with the Eastey VSA1825 Auto L-Sealer.

Eastey Value Series Shrink Tunnels are designed to produce superior shrinking on virtually any package. Variable speed air flow, air velocity and delayed cool down are just some of the features that provide the durability you have come to rely on from Eastey. See for yourself why Eastey has been a leader in the shrink packaging industry for over 35 years.

Standard Features

- Designed to shrink most polyolefin shrink films
- Live roller conveyor with silicone coated rollers provides a smooth finish
- 15kW heater with adjustable temperature control
- Tunnel temperature range between room temperature and 365°F (185°C)
- High velocity blower motors circulate air volume inside tunnel
- Variable air flow and air velocity for a variety of products and applications
- Tunnel window allows user to view product as it passes through tunnel and make adjustments as needed
- High quality cotton insulation keeps heat inside tunnel and minimizes energy consumption
- Delayed cool down and over temperature protection
- Conveyor speed up to 100 feet per minute
- Heavy-duty casters and leveling pads for transportation within plant
- Easy-to-use design requires minimal training, maintenance, and trouble free operation
- CE Certification

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the VST1710 Value Series Shrink Tunnel

Machine Dimensions			Chamber Dimensions			Conveyor Dimensions		Standard Power			Weight	Ship Wt.
Width	Height	Length	Width	Height	Length	Width	Length	Volts	Amps	Phase		
41.0" (1041mm)	49.5" (1257mm)	78.0" (1981mm)	18.0" (457mm)	10.0" (254mm)	59.0" (1499mm)	18" (457cm)	70.0" (1780mm)	200	30	3	800 lbs (363 kg)	900 lbs (408 kg)