



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal HDX-250 Heavy-Duty Combo L-Sealer

At a Glance

- 17 inch W x 21 inch L seal area
- RS-5 Plus digital controller
- Precise temperature controls

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Simple Combo L-Sealer for Demanding Production

The Heat Seal HDX-250 is designed for today's demanding requirements. Every component is top of the line from the film cradle to the RS-5 Plus digital controller, to the multiple knife profile seal bar, to the highly efficient shrink tunnel.

Features

Control Panel

Conveniently positioned, RS-5 Plus digital controller with three year warranty on original machine controller

Meets UL 508A Standard

Simple operation

Precise temperature controls

Cycle counter comes standard with reset

Single cord 220V single phase power supply

Sealing Area

Hot knife exact seal system with multiple profile options

Large 17"W x 21"L seal area

Cast aluminum seal head with stainless film clamps

Balanced magnetic hold down for strong, consistent seals

Seal conveyor with smooth product transfer from seal area to tunnel

Shrink Tunnel

Non-stick mesh belt with adjustable riser bar for improved bottom shrink
Efficient MaxAir tunnel almost triples the airflow and evenly wraps air around the package
Automatic cool down extends heating element life

Other Features

Package centering system for even shrink; sealing and tunnel conveyor move in tandem vertically
Tunnel horizontal quick slide adjustment
Auto-tensioning film cradle
Two year warranty
Heavy duty casters and levelers

Options

Fully stainless steel construction (HDX250S)
Left hand reverse flow
Heated hole punch
Powered film unwind with perforating roller and 6" adjustable inverting head
Spare parts kit (5820-012)
GTC180/16 180 degree gravity turn around conveyor
GTC90/16 90 degree gravity turn around conveyor
AT36 36" powered accumulator table
AT36 48" powered accumulator table

Specifications

Film Capacity: 22" Wide (56 cm)
L Bar Seal Area: 17"W x 21"L (43 W, 53 L cm)
Inside Tunnel Dimensions: 21"L x 16"W x 8"H (53 L, 41 W, 22 H cm)
Tunnel Conveyor Speed: 0-20 feet per minute (0-6 meters per minute)
Overall Dimensions: 82"L, 32"W, 59"H (208 L, 82 W, 150 H cm)
Working Height: 38" (97 cm)
Power Requirements: 208/220 Volts, 23 Amp, Single Phase
Tunnel Wattage: 3,100 Watts
Weight: 800 lbs (363 kg)
Estimated Shipping Weight: 900 lbs (409 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.