



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Heat Seal HDX-250A Automatic Combo L-Sealer



## At a Glance

- 20 inch W x 20 inch L seal area
- All electric, no compressed air needed
- Schneider electric control package
- Brushless servo-driven seal jaw

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Automatic Combo L-Sealer for Demanding Production

The compact Heat Seal HDX-250A automatic L sealer with integrated shrink tunnel is built on one frame to fit in tight spaces.

## Features

### Controls

- All electric, no air required
- 7" color touchscreen
- Store up to 128 recipes
- Multi-level password protection
- Multiple language
- Two emergency stop buttons
- USB & SD interface
- Variable speed conveyors

### Seal Area

- 20" x 20", one piece blade
- Closing conveyor
- Horizontal & vertical product sensors
- Adjustable seal jaw opening
- Adjustable seal pressure
- FDA belts

Slide on overhead film cradle

Overhead scrap rewind

### **Tunnel**

18"W x 10"H x 23"L chamber

Variable speed roller conveyor

Adjustable louvers

### **Other Features**

Compact design

Multiple alarms for machine monitoring

Powder coated steel construction

Locking casters

Two year limited warranty

## **Options**

2' gravity exit conveyor

PTFE mesh belt overlay for tunnel conveyor

Gravity turnaround conveyors available

Infeed conveyors, flighted or belted

## **Specifications**

Film Capacity: 23.5"W, 11.75"OD (600mmW, 300mmOD)

L Bar Seal Area: 20"W, 20"L (508mm W, 508mm L)

Tunnel Chamber: 18"W, 10"H, 23"L (458mmW, 254mmH, 585mmL)

Production Rate: Up to 20 PPM

Overall Dimensions: 95"L, 47"W, 67"H (2390mmL, 1190mmW, 1680mmH)

Maximum Product Dimension: 15.5"W, 16.5"L, 4.5"H (400mmW, 420mmL, 120mmH)

Power Requirements: 208-240VAC, 3Ph, 22A

Conveyor Height: 34.25" (870mm)

Weight: 1496 lbs (677 Kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.