



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Heat Seal HDX-350 Heavy-Duty Combo L-Sealer



## At a Glance

- 21 inch W x 25 inch L seal area
- RS-5 Plus digital controller
- Precise temperature controls

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Large Combo L-Sealer for Demanding Production

The Heat Seal HDX-350 is designed for today's demanding requirements. Every component is top of the line from the film cradle to the RS-5 Plus digital controller, to the multiple knife profile seal bar, to the highly efficient shrink tunnel.

## Features

### Control Panel

Conveniently positioned, RS-5 Plus digital controller with three year warranty on original machine controller

Meets UL 508A Standard

Simple operation

Precise temperature controls

Cycle counter comes standard with reset

Single cord 220V single phase power supply

### Sealing Area

Hot knife exact seal system with multiple profile options

Large 21"W x 25"L seal area

Cast aluminum seal head with stainless film clamps

Balanced magnetic hold down for strong, consistent seals

Seal conveyor with smooth product transfer from seal area to tunnel

### Shrink Tunnel

Non-stick mesh belt with adjustable riser bar for improved bottom shrink  
12" high tunnel opening  
Efficient MaxAir tunnel almost triples the airflow and evenly wraps air around the package  
Automatic cool down extends heating element life

## Other Features

Package centering system for even shrink; sealing and tunnel conveyor move in tandem vertically  
Tunnel horizontal quick slide adjustment  
Auto-tensioning film cradle  
Two year warranty  
Heavy duty casters and levelers

## Options

Powered film unwind with perforating roller and 10" high adjustable inverting head  
Fully stainless steel construction (HDX-250S)  
Left hand reverse flow  
ADD heated hole punch  
Scrap wind up  
Powered lift for seal conveyor  
Air actuating seal head  
E-stop  
Conveyor stop (in lieu of E-stop)  
PTFE non-stick mesh tunnel belt  
Stainless steel wire mesh tunnel belt  
Spare parts kit (5820-012)  
Export crating  
GTC180/16 180 degree gravity turn around conveyor  
GTC90/16 90 degree gravity turn around conveyor  
AT36 36" powered accumulator table

## Specifications

Film Capacity: 25" Wide (64 cm)  
L Bar Seal Area: 21"W x 25"L (53 W, 64 L cm)  
Inside Tunnel Dimensions: 27"L x 20"W x 12"H (69 L, 51 W, 30.5 H cm)  
Tunnel Conveyor Speed: 0-20 feet per minute (0-6 meters per minute)  
Overall Dimensions: 95"L, 35"W, 59"H (241 L, 89 W, 150 H cm)  
Working Height: 38" (97 cm)  
Power Requirements: 220 Volts, 60 Amp, Single Phase  
Tunnel Wattage: 6,200 Watts  
Weight: 1,080 lbs (490 kg)  
Estimated Shipping Weight: 1,230 lbs (558 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.