



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal Automatic Combo L-Sealer

At a Glance

- Up to 30 packages per minute
- 10 product presets for quick and easy product changeovers
- Multiple conveyor options

Buy your [shrink film](#) from us, and get a discount on this Heat Seal combo system!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Automatic Flexible Combo L-Sealer

Maximize productivity with Heat Seal's automatic combo shrink wrap packaging system. This automatic packaging system wraps up to 30 packages per minute. Flexible and reliable, this automatic shrink packaging system offers 10 product presets for quick and easy product changeovers.

This reliable Heat Seal combo automatic L-bar sealer and shrink tunnel system provides a quality shrink wrapping solution and will help lower packaging costs.

Features

IC-1772 Belted Infeed Conveyor

Power and control from HDSA-1721

Multiple conveyor options

Variable speed

Low pressure belt

HDSA1721 Automatic L-Sealer

Closing conveyor

PLC with color HMI controls

Wraps up to 30 packages per minute

T-3417 Shrink Tunnel

Digital temperature controls

Adjustable air flow

Options

Indexing motion profile with stop sensor (with flighted infeed conveyors)

FIC-1772- 6' flighted infeed conveyor, variable Speed

Package Dimensions

Length: 2.0" L Min. (5 cm) with closing conveyor

Width: 2" - 16" (5 - 41 cm)

Height: 0.13" - 4.75" (0.3 - 12 cm)

Specifications

HDSA-1721 Automatic L-Sealer

Film Capacity: 22" (55 cm) center folded, up to 44"(110 cm) with optional center folder

L Bar Seal Area: 17"W x 21"L (45 cm x 55 cm)

Conveyor Speed: 70 ft/min (21 m/min)

Overall Dimensions: 72"L x 38"W x 60"H (183 cm x 97 cm x 152 cm)

Working Adjustable: 32" - 36"

Height: (81 - 91 cm)

Power Requirements: 220VAC, Single Phase, 50/60 HZ, 8 A

Air Requirements: 2 cuft/min @ 80 psi (.085 cum/min @ 5.5 kg/sqcm)

Net Weight: 1020 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.