



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal HDX250A Automatic Combo L-Sealer

At a Glance

- 20 inch W x 20 inch L seal area
- All electric, no compressed air needed
- Schneider electric control package
- Brushless servo-driven seal jaw

Buy your [shrink film](#) from us, and get a discount on this Heat Seal L-sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Automatic Combo L-Sealer for Demanding Production

The compact Heat Seal HDX250A automatic L sealer with integrated shrink tunnel is built on one frame to fit in tight spaces.

Features

- All electric – no compressed air required
- Schneider electric control package; components available worldwide
- Work job settings program storage allows easy changeover
- Includes two E-stop buttons and other controls providing all-around safety protection
- Variable speed AC conveyor drives for accurate running adjustments
- Brushless servo-driven seal jaw with adjustable opening increases productivity
- Heavy-duty casters for portability
- 20" x 20" seal area with 10" high tunnel
- One year limited warranty

Specifications

- Film Capacity: 23.5"W, 11.75"OD (600mmW, 300mmOD)
- L Bar Seal Area: 20"W, 20"L (508mm W, 508mm L)
- Tunnel Chamber: 18"W, 10"H, 23"L (458mmW, 254mmH, 585mmL)
- Production Rate: Up to 20 PPM
- Overall Dimensions: 95"L, 47"W, 67"H (2390mmL, 1190mmW, 1680mmH)
- Maximum Product Dimension: 15.5"W, 16.5"L, 4-1/2"H (400mmW, 420mmL, 120mmH)

Power Requirements: 208-240VAC, 3Ph, 22A

Conveyor Height: 34.25" (870mm)

Weight: 1496 lbs (677 Kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.