



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal HDX2000 All Electric Automatic L-Sealer



At a Glance

- All electric system
- 15.5W x 23L inch seal area
- Dual gull wing with interlocked guarding
- Up to 60 packages per minute
- Schneider electric PLC and controls

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast All Electric Automatic L-Sealer

The complete Heat Seal HDX2000 all electric system comes with a fully integrated infeed conveyor which transfers product at just the right pitch and speed to maximize the potential of this shrink packaging system.

The automatic HDX2000 L-Bar sealer advances the package into the film with variable speed AC drive conveyors.

Features

Controls

- All electric, no air required
- Schneider electric PLC and controls, available worldwide
- Variable speed AC motors
- Plug and play set up
- Swing arm control panel, operate machine from either side
- Store up to 64 recipes, add your own photos
- Multi-level password protection
- Multiple language
- USB interface

Sealing Area

- 15.5"W x 23"L, one piece blade

Motorized movement of seal jaw opening and height and inverting triangle height
Adjustable seal force
Closing conveyor
Film loosening
Belt reversing
Seal cooling for polyethylene
FDA belts
Scrap rewind with scrap break and scrap full alarms

Other Features

Dual gull wing with interlocked guarding
Audible and visible alarms
Infeed and outfeed belts extend beyond machine opening
Interlocked slide out film carriage
Runs most polyolefin and polyethylene films
Horizontal and vertical product sensors
Powder coated steel construction
Casters and leveling pads
One year limited warranty

Specifications

Seal Area: 15.5"W, 23"L (400mmW, 600mmL)
Film Capacity: 27.5"W, 11.75"OD (700mmW, 300mmOD)
Conveyor Speed: Variable 20-100 FPM (6-30 mpm)
Production Rate: Up to 60 PPM
Maximum Product Dimension: 23.5"L, 15.5"W, 9.25"H (600mmL, 400mmW, 240mmH) Maximum dimensions cannot be used simultaneously
Power Requirements: 208-240 VAC, 1Ph, 15A
Conveyor Height: 34.25" TO 36.25" (870mm TO 920mm)
Overall Dimensions: 100"L, 49"W, 62"H (2518mmL, 1240mmW, 1558mmH)
Weight: 1265 lbs (573 Kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.