



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal HDX-3000 All Electric Automatic L-Sealer



At a Glance

- All electric system, no compressed air
- 15.5 wide seal area
- Dual gull wing with interlocked guarding
- Up to 40 packages per minute
- Brushless servo motors control hot knife and side seal system

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast All Electric Automatic L-Sealer

The complete Heat Seal HDX-3000 all electric side seal shrink system utilizes an intuitive HMI on a swing arm allowing the HDX-3000 to run right to left or left to right.

The automatic HDX-3000 L-Bar sealer uses brushless servo motors that control the hot knife and side seal system.

Features

- All electric, no air required
- Interlocked acrylic guard door with easy machine access
- Brushless servo motor controlled hot knife seal system
- Motorized adjustment of inverting head and seal height
- Swing arm control panel
- Plug and play set up
- 20-100 feet/min conveyor speeds, variable frequency AC drive

Other Features

- Motorized movement of seal opening, seal height, inverting triangle height
- Adjustable seal force
- Closing conveyor
- Seal cooling for polyethylene

- Extended infeed and outfeed belts
- Powder coated steel construction
- FDA approved belts
- Two individually adjustable film perforators
- Easy thread scrap rewind with scrap break and scrap film alarms
- Illuminated work area
- Casters and leveling pads
- Simple recipe storage
- Two year limited warranty

Options

- Infeed and outfeed conveyors
- Printer
- Clear product sensor
- Printed film registration sensor
- Electric film hole punch
- Product guides for unstable products

Specifications

- Seal Area: 15.5"W (400mmW)
- Film Capacity: 27.5"W, 11.75"OD (700mmW, 300mmOD)
- Conveyor Speed: Variable 20-100 FPM (6-30 mpm)
- Production Rate: Up to 40 PPM
- Maximum Product Dimension: 15.5"W, 9.25"H (600mmL, 400mmW, 240mmH) Maximum dimensions cannot be used simultaneously
- Power Requirements: 208-240 VAC, 1Ph, 10.5A
- Conveyor Height: 34.8" (880mm)
- Overall Dimensions: 100"L, 49"W, 62"H (2518mmL, 1240mmW, 1558mmH)
- Weight: 1940 lbs (880 Kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.