



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal HS2030 Standard-Duty Semi-Automatic L-Sealer



At a Glance

- 20 inch x 30 inch seal area
- Impulse wire sealing system
- Single plug 115V power supply

Buy your [shrink film](#) from us, and get a discount on this Heat Seal L-sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Flexible Reliable Automatic L-Sealer

The Heat Seal HS2030 standard-duty semi-auto shrink system has a 20" x 30" seal area. This shrink wrap equipment utilizes a hot wire sealing system.

Features

Control Panel

Express control panel for machine operations
Single plug 115V power supply

Sealing Area

Impulse wire seal system
Standard-duty seal head design with film clamps
Magnetic hold down with adjustable pressure and dwell time
Adjustable height wrapping platform

Other Features

One year warranty
Heavy gauge steel construction
Console leg kit with 3" locking casters
Adjustable film cradle
Individually adjustable perforating wheels

Options

Stainless steel construction
Spare parts kit
Posi-trac seal conveyor
Stand alone power scrap wind-up
Export crating

Specifications

Film Capacity: 22" Wide (56 cm)
L Bar Seal Area: 20"W x 30"L
Overall Dimensions: 65"L x 29"W x 59"H
Working Height: 35" (89 cm)
Weight: 230 lbs (105 kg)
Power Requirements: 115 Volts, 17 Amp

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.