



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal T-2016 Compact Shrink Heat Tunnel



At a Glance

- 20 inch L x 15 inch W x 6 inch H chamber dimensions
- Single chamber design
- Heavy-gauge steel construction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact Shrink Tunnel

Heat Seal T-2016 compact shrink heat tunnels are designed for low-volume application of tamper-evident shrink bands.

Features

Tunnel Chamber

Inside Tunnel Dimensions: 20"L x 15"W x 6"H

6.5"H x 15"W tunnel opening

Single chamber design

Analog tunnel temperature control

High-velocity turbo tunnel design

Automatic cool down extends heating element life

Built in high-temperature limit switch

Conveyor

Variable speed, non-stick mesh tunnel belt

Conveyor speeds up to 25 FPM

Transition conveyor

Other Features

Heavy gauge steel construction

One year warranty

Options

Stainless steel construction

Painted console leg kit with 3" casters

Stainless console leg kit with 3" casters

Specifications

Inside Tunnel Dimensions: 20"L x 16"W x 6.5"H (51cm L x 40cm W x 16.5cm H)

Conveyor Speed: 0 - 25 ft/min (0 - 7.6 m/min)

Conveyor: Variable speed, non-stick mesh belt

Overall Dimensions: 40"L x 20"W x 48"H (102L x 51W x 1225H cm)

Weight: 172 lbs (78 kg)

Power Requirements: 115 Volts, 20 Amps, Single Phase

Wattage: 2,000 Watts

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.