



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Heat Seal T-3422 Shrink Heat Tunnel



## At a Glance

- 34 inch L x 22 inch W x 10 inch H chamber dimensions
- High-velocity air flow with dual mechanical controls
- Two heat zones

Buy your [shrink film](#) from us, and get a discount on this Heat Seal shrink tunnel!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Mid-Volume Heat Shrink Tunnel

Heat Seal T-3422 Shrink Heat Tunnels are designed for large capacity applications with a 34"L x 22"W x 10"H chamber.

## Features

### Tunnel Chamber

Inside Tunnel Dimensions: 34"L x 22"W x 10"H

Digital tunnel temperature control

High-velocity air flow with dual mechanical controls

Open coil heating element guaranteed for 10 years

Two heat zones

High-temperature limit switch

Automatic cool down extends heating element life

### Conveyor Features

Quick change 0.5" diameter live/dead rollers with 2" spacing

Unique pre-shrink feature allows for 25% more bottom shrink

One-quarter horsepower motor with adjustable conveyor speeds of up to 70 feet per minute

## Other Features

Heavy gauge adjustable height console with levelers and 3" casters

Two year warranty

## Options

Stainless steel construction

Stainless steel wire mesh belt conveyor  
Non-stick mesh belt conveyor  
1" or 1.5" roller spacing  
14" high tunnel opening  
Pack cooler fan for polyethylene  
Hydraulic easy lift adjustable height console  
Left hand reverse flow  
Export crating

## Specifications

Inside Tunnel Dimensions: 34"L x 22"W x 10"H (86L x 56W x 25H cm)  
Conveyor Speed: 0 - 30 ft/min (0 - 9 m/min)  
Conveyor: Variable speed, quick change live/dead silicone covered rollers with 2" spacing  
Overall Dimensions: 60"L x 31"W x 57"H (153L x 79W x 145H cm)  
Weight: 560 lbs (255 kg)  
Power Requirements: 220 Volts, 54 Amps, Single Phase  
Wattage: 10,000 Watts

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.