



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Heat Seal TX5218 Heavy-Duty Shrink Heat Tunnel



## At a Glance

- 52 inch L x 17.5 inch W x 8 inch H chamber dimensions
- Two-chamber design with dual temperature control
- Digital temperature adjustment with 9 customized program settings

Buy your [shrink film](#) from us, and get a discount on this Heat Seal shrink tunnel!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Console Compact Tamper Band Shrink Tunnel

The Heat Seal TX5218 high-speed dual chamber shrink tunnel features separate temperature controls and adjustable air baffles for each chamber.

## Features

### Tunnel Chamber

Inside tunnel dimensions: 52"L x 17.5"W x 8"H

Two-chamber design with dual temperature control

Digital temperature adjustment with 9 customized program settings

Adjustable air flow

High-temperature safety alarm

Automatic cool down

Schneider electric components

### Conveyor

Digital variable speed

Live/Dead selection roller conveyor

3/8" (10mm) OD roller on 1" (25mm) pitch

20" (50cm) roller exit conveyor

## Other Features

Powder coated steel construction

Heavy-duty locking casters

One year warranty

## Specifications

Inside Tunnel Dimensions: 52"L x 17.5"W x 8"H (134cm L x 45cm W x 21cm H)

Conveyor: Variable speed quick change, live/dead rollers, 34"H

Power Requirements: 208-240 VAC, 3Ph, 14 kW - 43A @208VAC, 49A @240VAC

Overall Dimensions: 64.5"L x 31.5"W x 57.5"H (163cm L x 80cm W x 146cm H)

Weight: 574 lbs (260 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.