Professional Packaging Systems
2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact
Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal T-3422 Shrink Heat Tunnel

At a Glance

- 34 inch L x 22 inch W x 10 inch H chamber dimensions
- High-velocity air flow with dual mechanical controls
- Two heat zones

Buy your shrink film from us, and get a discount on this Heat Seal shrink tunnel!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Mid-Volume Heat Shrink Tunnel

Heat Seal T-3422 Shrink Heat Tunnels are designed for large capacity applications with a 34"L x 22"W x 10"H chamber.

Features

Tunnel Chamber
Inside Tunnel Dimensions: 34"L x 22"W x 10"H
Digital tunnel temperature control
High-velocity air flow with dual mechanical controls
Open coil heating element guaranteed for 10 years
Two heat zones
High-temperature limit switch
Automatic cool down extends heating element life
Conveyor Features
Quick change 0.5" diameter live/dead rollers with 2" spacing
Unique pre-shrink feature allows for 25% more bottom shrink
One-quarter horsepower motor with adjustable conveyor speeds of up to 70 feet per minute

Other Features

Heavy gauge adjustable height console with levelers and 3" casters
Two year warranty

Options

Stainless steel construction

Copyright © 2024 Professional Packaging Systems

Stainless steel wire mesh belt conveyor
Non-stick mesh belt conveyor
1" or 1.5" roller spacing
14" high tunnel opening
Pack cooler fan for polyethylene
Hydraulic easy lift adjustable height console
Left hand reverse flow
Export crating

Specifications

Inside Tunnel Dimensions: 34"L x 22"W x 10"H (86L x 56W x 25H cm)
Conveyor Speed: 0 - 30 ft/min (0 - 9 m/min)
Conveyor: Variable speed, quick change live/dead silicone covered rollers with 2" spacing
Overall Dimensions: 60"L x 31"W x 57"H (153L x 79W x 145H cm)
Weight: 560 lbs (255 kg)
Power Requirements: 220 Volts, 54 Amps, Single Phase
Wattage: 10,000 Watts

Please contact Pro Pac or call 888-318-0083 for your shrink equipment.

Copyright © 2024 Professional Packaging Systems