



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Shanklin Omni Form-Fill Seal Shrink Wrapper

## At a Glance

- Modular plug-and-play infeeds
- Maximum packaging flexibility
- Servo motion-control technology

Buy your [shrink film](#) from us, and get a discount on this Shanklin shrink equipment!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



## Innovative Form Fill Seal Shrink System

Omni form-fill seal shrink wrappers redefine traditional shrink packaging equipment with innovative new features like modular plug and play infeeds, advanced control network, and dual product flow configurations. Designed for maximum packaging flexibility and ease of operation, the Omni begins the next generation of shrink packaging equipment.

## Smart, Friendly Features

Touch-screen provides easy system setup and operation.

Operator interface features English, Spanish and French.

Enter new package dimensions and the recipe calculator will assist with setup.

Viewable fault log tracks system errors.

Secure multi-level security access.

Store up to 100 recipes for quick, repeatable changeovers at the touch of a button.

Intelligent control network automatically identifies attached infeed module and accessories, and configures system accordingly.

Easy access to all areas of machine. Light-weight, easy-open seal-area cover, three front-hinged access panels (wrapper, selvage, and infeed) and a rear swing-out electrical control cabinet.

Quick-release conveyor belt rollers, and fault identification and history.

## Versatile Sealing System with Plug and Play Infeeds

Versatile large-capacity sealing system has wide and high end-seal opening allows plenty of room to package large, tall products.

Choose either EZ Open dual wire or hot knife sideseal assembly, and SmartWire or hot knife end-seal assembly.

Servo motion-control technology provides fast, high-speed packaging speeds. Adjustable end-seal pressure, film bunching for tall products, automatic positioning for end-seal opening, end-seal centerline, side-seal conveyor positioning and side-seal centerline. Plug-and-play infeed modules may be purchased separately as needed, giving you longterm flexibility, value and investment protection. Quick infeed changeovers in less than 10 minutes.

## Choose the Infeed Module that Maximizes Your Production

- [Omni RL with Single-Belt Infeed](#)
- [Omni LR with Dual-Belt Infeed](#)
- [Omni LR with Harmonic Infeed](#)
- [Omni RL with Flighted Infeed](#)

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

## Features of the Omni-G and Omni-S Models

Features	Omni-G	Omni-S
23" Wide End Seal	X	X
8" High End-Seal Opening	X	
10" High End-Seal Opening		X
Dual End-Seal Eyes	X	X
EZ Open Dual Wire or Hot Knife Side Seal	X	X
Modular Infeed Connection Ports	X	X
Automatic System Configuration	X	X
Enable/Disable Infeed Capability	X	X
Left-to-Right Product Flow Configuration	X	X
Light Stack Status Indicator	X	X
Quick Release Conveyor Belt Rollers	X	X
Casters	X	X
Graphics-Based Color Touch Screen	X	X
100-Package Recipe Storage Capacity	X	X
Quick Set-Up Recipe Calculator	X	X

CE-Compliant Design	X	X
Multilingual Operator Interface	X	X
Metric Fasteners	X	X
Swing-Out Electrical Control Cabinet	X	X
Integrated Recessed Selvage Winder with Dancer-Controlled Variable Speed Drive	X	X
Selvage Full Alarm / Blue Indicator Light	X	X
Selvage Break Alarm / Machine Stop	X	X
Automatic Scrap Film Threading (Air assist on start-up only)	X	X
Programmable "Film Bunching" for Tall Products	X	X
Dual-Axis Servo End Seal		X
Programmable End-Seal Pressure		X
Automatic Positioning for End-Seal Opening and Centerline		X
Automatic Positioning for Side-Seal Conveyor and Centerline		X