



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Shanklin Triumph TR-2 Automatic Shrink Wrapper



## At a Glance

- Up to 70 packages per minute
- Generates product spacing on-the-fly from randomly presented products
- Maximum accessibility for easy cleaning, troubleshooting and maintenance

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Smarter, Faster, Taller, Flexible, Easy to Operate

Inspired by the robust and functional design of the original Triumph Wrapper, the Shanklin Triumph TR-2 automatic form-fill-seal wrapper is a perfect mid-range solution for applications that require more advanced features than an L-Sealer, but fewer than those typically required on a high speed automatic wrapper.

Packed with a huge list of standard features, built to last and affordably priced, the Shanklin Triumph TR-2 is easily one of the best shrink packaging values available on the market today.

## Machine Features

Manual package adjustments utilize digital indicator displays and linear scale positions that are useful in recipe recall to allow for repeatability and quick set up.

EZ Load unwind allows for easy loading and change over of rolls of film.

General purpose brush backed pin perforator is convenient, modular and easily adjustable to optimize air evacuation.

Recessed selvage winder places the selvage removal process conveniently within the structure of the machine.

Light stack indicates important machine status (stop, ready, run mode, and need for attention).

Easy toolless adjustments for inverting head, end seal height, side seal height, infeed conveyor and package guides.

Selvage full alarm indicates warning on light stack and stops machine after an adjustable time delay.

Selvage break alarm stops machine and indicates occurrence on light post.

On-board diagnostics, and modular construction provide reduced downtime.

Maintains right-to-left product flow direction of the Automatic L-Sealer with virtually the same footprint.

Dependable and reliable AC Drive motors.

Quick-disconnect electrical sensors features LED telltale connectors with quick disconnect plugs to aid in troubleshooting and maintenance.

Swing-Out electrical box provides easy access to traditionally hard to access areas of the machine.

Ethernet-ready for network connectivity.

Batch counters counts machine cycles or can incorporate an external input to count finished case units.

Smart carriage feature allows the machine speed to be adjusted without affecting end seal settings.

Multi-language operator interface with 8 languages: English, French, Spanish, Polish, Italian, German, Portuguese and Russian.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

# Specifications of the Triumph TR-2 Shrink Wrap Machine

Package Size	Minimum 2"W x .125"H x 3"L Maximum 15"W x 5"H x 48"L Width + height combination cannot exceed 17"
Maximum Film Width	21" folded or 42" flat, centerfolder required
Conveyor Height	32.5" to 40.5"
Package Speeds	Up to 70 jaw cycles per minute
Film Speeds	Up to 90 linear feet per minute
Longitudinal Seal	Weld bead at side of package
Transverse Seal	SmartWire or wide fin hot knife jaws
Main Drive	3/4 HP AC motor with AC inverter variable speed drive
Infeed Drive	3/4 HP AC motor with AC inverter variable speed drive
Power	230 volts, 30 amps, 1 phase, 50/60 hz
Compressed Air	3 CFM free air at 70 psi
Foot Print	56.5"W x 93"L
Ship Weight	1896 lbs
Safety Devices	Emergency stops Seal jaw safety switches Protective guards Safety interlocks on all access panels
Accessories	Casters EZ Load infeed table Venturi vacuum scrap transfer Level bottom jaw with short product transfer Print registration EZ load compact centerfolder Dual roll compact centerfolder Wide belt infeed conveyor Flight bar infeed conveyor Flight lug infeed conveyor