



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Shanklin A-26i Automatic L-Sealer Shrink Wrapper



At a Glance

- Up to 35 packages per minute
- 15 inch width x 21 inch length seal size
- 24 inch maximum centerfold film width

Buy your [shrink film](#) from us, and get a discount on this Shanklin shrink equipment!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast Automatic Shrink System with 15" x 20" Seal Area

The A-26i features adjustable height seal jaws and can automatically wrap a wide range of products, including high profile or short length items, at speeds up to 35 packages per minute. It is also available in a USDA approved model.

Features of the Shanklin A-26i, A-27i, and A-28A L-Sealers

Programmable controllers for simplicity of wiring, ease of troubleshooting, and easy machine set-up and adjustment.

Photo-electric sensor system automatically compensates for package length change.

Automatic film advance system allows light, flexible products to be fed through the machine with ease.

Easy product and size changeover.

Handles virtually any type of shrink film (depending on sealing system).

Most features are fully-adjustable for maximum convenience.

Electrical controls are UL-listed for meeting the highest safety standards.

Sealing area is protected by an electrically interlocked transparent hood through which the sealing process may be safely observed; hood is easily lifted for full access when necessary.

Secure password protection capability safeguards sensitive machine functions.

EZ-load unwind feature offers easy loading and threading capability.

Machine controls are located in front for quick and easy access.

New Touchscreen for A-26i and A-27i

Picture-based navigation

Corrective action
Recipe parameters
Batch / lifetime counting
Languages
Operator lock out options
Input / output status screens
Conveyor calibration screens
Imperial / metric switching
Status timers

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the A-26i, A-27i, and A-28A L-Sealers

Specification	A-26i	A-27i	A-28A
Seal Size	15"W x 21"L	21"W x 33"L	31"W x 43"L
Maximum Product Height	5.5"	7.5" (9.5" optional)	9.5"
Minimum Product Length	4" Standard 1.5" with optional closing conveyor	4" standard 2.75" with optional closing conveyor	7.5" standard 5" with optional closing conveyor
Maximum Product Length	20"	31"	41"
Maximum Film Width (Folded)	24"	30"	36"
Maximum Film Width (Flat)	44" with compact centerfolder	44" with compact centerfolder	60" with large compact centerfolder
Packaging Speeds	Up to 35 packages per minute	Up to 35 packages per minute	Up to 25 packages per minute
Longitudinal and Transverse Seal	Wide fin hot knife	Wide fin hot knife	Wide fin hot knife
Conveyor Height	Adjustable 31.5" - 37.5"	Adjustable 31.5" - 37.5"	Adjustable 31.5" - 37.5"
Power	230V, 15 Amps, 60 Hz, 1 phase	230V, 15 Amps, 60 Hz, 1 phase	230V, 15 Amps, 60 Hz, 1 phase
Compressed Air	0.5 CFM free air at 60 PSI	0.5 CFM free air at 60 PSI	0.5 CFM free air at 60 PSI
Safety Devices	<p>Emergency stop button instantly stops all machine functions until manually reset</p> <p>A transparent hood, interlocked electrically with the automatic sequencing circuit, covers the sealing area; gas cylinders support the hood when it is lifted to allow access</p> <p>Film clamp proximity sensors ensure safe sealing arm jaw closure</p> <p>Multiple safety interlocks</p> <p>Tamper-resistant controls</p> <p>Low voltage sensors and actuators</p>		

Options of the A-26i, A-27i, and A-28A Models

By selecting just the right combination of options, you can customize your Shanklin A-Series Automatic L-Sealer for the ultimate performance, efficiency and value!

Options	A-26i	A-27i	A-28A
Adjustable Flight Bar Infeed Conveyor	X	X	
Adjustable Flight Lug Infeed Conveyor	X	X	
Product Separating Infeed Conveyor	X	X	X
Closing Discharge Conveyor	X	X	X
Product Pressure Rollers over the Discharge Conveyor	X	X	X
EZ Load Compact Centerfolder	X	X	X
Dual Roll Compact Centerfolder	X	X	X
Dual Infeed Eyes	X	X	X
Print Registration	X	X	X
Discharge Rollers for Light Product	X	X	X
Casters	X	X	X
SmartWire Seal Jaws (in lieu of Hot Knife Jaws)	X	X	
EZ Film Thread Infeed Table	X	Standard	