



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Shanklin A-28A Automatic L-Sealer Shrink Wrapper

At a Glance

- Up to 25 packages per minute
- 31 inch width x 43 inch length seal size
- 36 inch maximum centerfold film width

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Automatic Shrink System for Heavy Products with 31" x 43" Seal Area

The large-capacity workhorse model of the Shanklin A-Series, the A-28A features adjustable height seal jaws specially-designed for products too large to fit through the A-26i or A-27i. This model is also equipped with a heavy-duty discharge conveyor to wrap much heavier product than most automatic L-Sealers can handle.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the A-26i, A-27i, and A-28A L-Sealers

Specification	A-26i	A-27i	A-28A"
Seal Size	15"W x 21"L	21"W x 33"L	31"W x 43"L
Maximum Product Height	5.5"	7.5" (9.5" optional)	9.5"
Minimum Product Length	4" Standard1.5" with optional closing conveyor	4" standard2.75" with optional closing conveyor	7.5" standard5" with optional closing conveyor
Maximum Product Length	20"	31"	41"
Maximum Film Width (Folded)	24"	30"	36"
Maximum Film Width (Flat)	44" with compact centerfolder	44" with compact centerfolder	60" with large compact centerfolder
Packaging Speeds	Up to 35 packages per minute	Up to 35 packages per minute	Up to 25 packages per minute
Longitudinal and Transverse Seal	Wide fin hot knife	Wide fin hot knife	Wide fin hot knife
Conveyor Height	Adjustable 31.5" - 37.5"	Adjustable 31.5" - 37.5"	Adjustable 31.5" - 37.5"
Power	230V, 15 Amps, 60 Hz, 1 phase	230V, 15 Amps, 60 Hz, 1 phase	230V, 15 Amps, 60 Hz, 1 phase
Compressed Air	0.5 CFM free air at 60 PSI	0.5 CFM free air at 60 PSI	0.5 CFM free air at 60 PSI
Safety Devices	Emergency stop button instantly stops all machine functions until manually reset A transparent hood, interlocked electrically with the automatic sequencing circuit, covers the sealing area; gas cylinders support the hood when it is lifted to allow access Film clamp proximity sensors ensure safe sealing arm jaw closure Multiple safety interlocks Tamper-resistant controls Low voltage sensors and actuators		

Options of the A-26i, A-27i, and A-28A Models

By selecting just the right combination of options, you can customize your Shanklin A-Series Automatic L-Sealer for the ultimate performance, efficiency and value!

Options	A-26i	A-27i	A-28A
Adjustable Flight Bar Infeed Conveyor	X	X	
Adjustable Flight Lug Infeed Conveyor	X	X	
Product Separating Infeed Conveyor	X	X	X
Closing Discharge Conveyor	X	X	X
Product Pressure Rollers over the Discharge Conveyor	X	X	X
EZ Load Compact Centerfolder	X	X	X
Dual Roll Compact Centerfolder	X	X	X
Dual Infeed Eyes	X	X	X
Print Registration	X	X	X
Discharge Rollers for Light Product	X	X	X
Casters	X	X	X
SmartWire Seal Jaws (in lieu of Hot Knife Jaws)	X	X	
EZ Film Thread Infeed Table	X	Standard	