



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Texwrap Double Chamber Shrink Heat Tunnels



At a Glance

- Double chamber heat tunnel
- Continuous-duty industrial grade blower motor
- Well-insulated energy efficient design
- Digital temperature controls, high-velocity fans, top and bottom air controls, and variable speed conveyors

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Double Chamber Forced Air Tunnels Give Outstanding Shrink Results

Texwrap double-chamber forced air convection tunnels are designed to give outstanding shrink results on medium speed applications. Texwrap forced air tunnels have proven over years of use to produce excellent results.

Generally paired with an L-sealer or intermittent motion wrapper, this type of tunnel uses large volumes of high-velocity air to film for the best shrink package.

Digital temperature controls, high-velocity fans, individual top and bottom controls for air direction, and variable speed conveyors all contribute to precisely control the right amount of heat to the right places over the correct amount of time - producing outstanding shrink results.

Features

- Continuous-duty industrial grade blower motor.
- Air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink.
- Durable powder coat finish.
- Selectable on/off and P.I.D. control with auto-tuning of proportional band.
- Tamper proof setting, faulty sensor compensation and controller diagnostics.
- Easy-to-read LED display.
- Well-insulated energy efficient design.
- AC direct drive motor with variable speed control for conveyor speed.

- Audible high heat alarm and high heat limit thermostat.
- Stainless steel mesh belt standard.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of Texwrap Double Chamber Tunnels

	ST-1322/2	STB-1432/2
Opening	13"H x 22"W	14"H x 32"W
Conveyor Width	15"	24"
Conveyor Height	33"-37.5"	33"-35"
Chamber Length	85"	111"
Conveyor Speed per Minute	0 - 160	0 - 160
Heaters	6 Flange Cal-Rod	6 Flange Cal-Rod
Electrical	240V, 3Ph, 65Amp	480V, 3Ph, 37Amp
Dimensions	133"L x 45.5"W x 76-81"H	159"L x 55"W x 78-83"H
Shipping Weight	1820 lbs	2000 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.