



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Texwrap Triple Chamber Shrink Heat Tunnels



## At a Glance

- Triple chamber heat tunnel
- Continuous-duty industrial grade blower motor
- Well-insulated energy efficient design
- Digital temperature controls, high-velocity fans, top and bottom air controls, and variable speed conveyors

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Triple Chamber Forced Air Tunnels Give Outstanding Shrink Results

Texwrap triple-chamber forced air convection tunnels are designed to give outstanding shrink results on high speed applications. Texwrap forced air tunnels have proven over years of use to produce excellent results.

Generally paired with a high-speed or servo continuous motion wrapper, this type of tunnel uses large volumes of high-velocity air to film for the best shrink package.

Digital temperature controls, high-velocity fans, individual top and bottom controls for air direction, and variable speed conveyors all contribute to precisely control the right amount of heat to the right places over the correct amount of time - producing outstanding shrink results.

## Features

- Continuous-duty industrial grade blower motor.
- Air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink.
- Durable powder coat finish.
- Selectable on/off and P.I.D. control with auto-tuning of proportional band.
- Tamper proof setting, faulty sensor compensation and controller diagnostics.
- Easy-to-read LED display.
- Well-insulated energy efficient design.
- Audible high heat alarm and high heat limit thermostat.

- Stainless steel mesh belt standard.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

## Specifications of Texwrap Triple Chamber Tunnels

	ST-1322/3	STB-1432/3
Opening	13"H x 22"W	14"H x 32"W
Conveyor Width	15"	24"
Conveyor Height	31.5"-37"	31.5"-37"
Chamber Length	127.5"	174"
Conveyor Speed per Minute	0 - 250	0 - 250
Heaters	9 Flange Cal-Rod	9 Flange Cal-Rod
Electrical	480V, 3Ph, 70Amp	480V, 3Ph, 99Amp
Dimensions	177"L x 34.625"W	XXX"L x XX"W
Shipping Weight	2500 lbs	3000 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.