



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Texwrap Spartan 2215 L-Sealer Shrink Wrapper



At a Glance

- Up to 30 packages per minute
- Max package size 19in x 15.5in x 5in
- 28 inch maximum centerfold film width

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Robust, Compact, Affordable L-Sealer

The Texwrap Spartan ST-2215 L-sealer offers a small footprint, ease-of-operation, and a quick return on investment.

The Spartan ST-2215 runs a wide range of product sizes. Adjustable 20 to 80 feet-per-minute conveyors work in concert with Texwrap exclusive motion trim technology, satisfy production requirements in a wide variety of applications.

Designed specifically to compete with lower-priced imports, the robust Texwrap Spartan L-sealer comes standard with many features not usually found on machines in this price range.

Built in the USA, the Texwrap Spartan 2215 L-sealer provides Texwrap proven design and reliability.

Benefits

- Space saving design
- Light to medium duty applications
- Simple to operate
- Laser-cut, heavy steel-frame construction with durable powder-coat finish
- Maximum film/belt speed 80 FPM for faster throughput
- 115 volt AC power allows the wrapper to be used with a standard wall outlet
- Eye-level, easy-reach film scrap winder with film break alarm
- Compact size allows operation in crowded production areas

- Made in USA

Features

- Texwrap exclusive Motion Trim control allows higher production speeds
- Constant-run capability allows the infeed conveyor to run continuously for faster product feeding
- Mushroom seal with one-piece knife for clean cuts, even in the corner
- Hand wheel on inverter for easy package height adjustment
- Tool-adjustable seal height
- HMI panel with simple menus for easy operation
- Individual solid-state temperature controls for side and cross seal
- Variable-speed, VFD inverter-duty AC motors
- Independent front and rear bag length settings
- Complete guarding package with safety interlocks
- Microperf pin perforator for precise air evacuation
- Film clamps with safety switches
- Leveling legs with casters

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the Spartan 2215 L-Sealer

Packages per Minute	Up to 30
Conveyor Width	15.5"W
Cross Seal Width	18.5"W
Minimum Package Size	4"L x 2"W
Maximum Package Size	19"L x 15.5"W x 5"H
Maximum Film Width	28" Center Fold
Conveyor Height	Adjustable From 33"-35"
Electrical	115V, 15 Amp
Air	3 CFM @ 80 PSI
Footprint	78.625"L x 37.625"W x 60

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.