



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Texwrap TLS 2219 & 3322 L-Sealer Shrink Wrapper



At a Glance

- Conveyor speeds of 20 to 100 feet per minute
- Max package size 19in x 15.5in x 9in
- 28 inch maximum centerfold film width

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast, Automatic-Indexing L-Sealer

Texwrap 2219 and larger 3322 intermittent motion L-seal systems are easy-to-use and built for constant operation.

Texwrap TLS 2219 and 3322 L-sealers come standard with features not available on competitive models in this price range. These premium features include low-mount film cradle, swivel operator panel, touchscreen library to easily recall package setups, and automatic dwell time compensator.

The Texwrap TLS 2219 and 3322 L-sealers include a fully-automatic product indexing and package length adjustment by either horizontal or vertical electric eye to accommodate most package configurations.

Built in the USA, the Texwrap TLS L-sealer provides Texwrap proven design and reliability.

TLS L-Sealer Key Features

Fast Production Speeds Texwrap exclusive Motion Trim technology and 100 FPM conveyor speeds make these L-sealers incredibly fast.

User Friendly Interface Allen Bradley controls, restricted service-level menus, and AC VFD drives make Texwrap TLS L-sealers popular with maintenance staff and operators.

Corrosion-Resistant Options Texwrap TLS L-sealers are also available in corrosion resistant stainless steel models that are designed for harsh or wet environments. Texwrap also offers infeeds and tunnels

in stainless versions, as well.

Multi-Packing L-Sealer

Multi-packing products in shrink film often eliminates the need for chipboard pads or trays.

Texwrap TLS L-sealers programmable multi-pack auto-collates and wraps single lane multi-packs. The program is simply set for the desired number of units per row. A pusher bar is activated when that number is reached.

The pusher bar can be set for the number of rows desired and is only limited by the size of the sealing area. An right angle pusher is another great option to create multi-pack configurations.

Benefits

Texwrap patented Motion Trim technology increases throughput by running infeed and exit conveyors while seal jaws are in motion.

Auto-reversing belt relaxes film, creates better seals, and reduces film usage especially with tall products.

Standard pass-through feature allows product to move through machine without shrink wrapping the product.

Programmable multi-pack feature auto-collates and wraps single lane multi-packs.

Contains a clean corner cut tail removal that cleanly cuts film tail by squaring the package prior to sealing. Results are consistently strong seals and superior aesthetics.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of TLS 2219 & 3322 L-Sealers

	TLS-2219	TLS-3322
Max Package Size	9"H x 15.5"W x 19"L (standard) 7"H x 15.5"W x 19"L (closing conveyor)	10.5"H x 19.5"W x 32"L (standard) 8.5"H x 19.5"W x 32"L (closing conveyor)
Max Film Width	28" Center Fold	28" Center Fold
Min Film Width	6" Center Fold	6" Center Fold
Conveyor Speed	20 to 100 feet per minute	20 to 100 feet per minute
Construction	Heavy-duty welded tubular steel standard (corrosion resistant optional)	
Orientation	Right or left hand configuration	

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.