



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Texwrap LSS Lap Seal Shrink Wrappers



At a Glance

- For shrink wrapping long runs of constant-sized products
- Accommodates thermo seal lap seal, static seal lap seal, and thermo static lap seal
- Maximum conveyor speed 200 FPM

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast Horizontal Lap Sealers

Texwrap LSS lap sealers are the fastest and most flexible wrappers for shrink bundling applications requiring high-speed bundling packages where a bottom lap seal is desired.

Texwrap LSS lap sealers accommodate thermo seal lap seal, static seal lap seal, and thermo static lap seal either as operator options within the same machine or dedicated to one type depending on the application. Texwrap LSS lap sealers come with an overhead film cradle, or an optional floor mount cradle with manual splice or dual-cradle auto splice.

Shrink Wrapping Same-Size Products

Lap sealers are popular for shrink bundling applications which call for long runs of constant-sized products because each product requires an individually-sized plow as well as a specific width of film to be stocked.

Lap seal wrappers place a nearly invisible overlap seal under the package making a very attractive package while using the minimum width film.

Lap sealers use flat single wound film which is pulled over a forming plow, overlapped under the package and sealed by use of either a static or thermal seal. As the products flow through the former, they are encapsulated in a continuous tube of film and cut apart downstream by the end seal device.

Features

- Maximum conveyor speed 200 FPM

- Patented orbital servo head design keeps blade and pad vertical through entire range of motion making tighter packages and reducing film usage
- Heated bottom seal pad
- Variable-speed, inverter-duty AC motors
- Overhead, powered-nip-roller film delivery system
- Maximum 40" wide flat film
- Variable speed, servo-controlled exit conveyor to relax bridged film at cross seal
- Optional film splicing available
- Multiple seal options: static, thermal, combinations, etc

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of LSS Lap Sealers

| | LSS-1407 | LSS-1809 | LSS-145 |
|------------------|--|---------------------------|-----------------------------|
| Max Package Size | 7"H x 14"WInfinite length | 9"H x 18"WInfinite length | 4.5"H x 14"WInfinite length |
| Max Film Width | 48" Single wound | 54" Single wound | 48" Single wound |
| Conveyor Speed | Up to 140 feet per minute | Up to 140 feet per minute | Up to 200 feet per minute |
| Footprint | 123"L x 69"W | 134"L x 73"W | 118"L x 70"W |
| Construction | Heavy-duty welded tubular steel standard Optional corrosion resistant design | | |
| Orientation | Right or left hand configuration | | |

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.