



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Texwrap OSS Orbital Side Seal Shrink Wrappers



At a Glance

- Fast, precise servo controls with an elliptical motion sealing head
- Designed for special requirements of a fast food and bakery production environment
- OSS orbital side sealer the fastest and most flexible wrapper of its kind

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Super High-Speed Continuous-Motion Side Sealer

Texwrap OSS orbital seal head wrappers are designed for special requirements of a food production environment, including fast paced bakery applications demanding the highest productions rates.

Corrosion resistant design features stainless steel construction and a removable washdown infeed.

Texwrap OSS orbital seal head wrappers combine very fast, precise servo controls with an elliptical motion sealing head. This motion allows extremely fast speeds by drastically reducing the movement needed by the head in order to make the seal.

This orbital design combined with the 200 feet per minute conveyor speed and Texwrap exclusive Motion Trim technology make the OSS orbital side sealer the fastest and most flexible wrapper of its kind.

Features

Orbital Seal System Utilizing Texwrap's patented Orbital Seal System results in highest rate of speed at continuous operation.

Servo Controlled Seal Jaw The seal jaw is servo controlled for precise seal placement.

Texwrap Designed Product Infeed Utilizing its library of infeed designs Texwrap will configure a solution to optimize product output.

Centerline Justified Easily paired with Texwrap infeed to provide a precise, consistent flow of product into the wrapper.

Precise Product Control Finely tuned product control through the transition zones to maximize seal strength and quality.

OSS-145

Texwrap OSS-145 continuous motion orbital side sealers are designed for applications requiring high-speed wrapping of packages where a side seal is desired.

The Texwrap patented servo orbital head combined with the 200 feet per minute conveyor speed and Texwrap's exclusive Motion Trim technology make the OSS-145 the fastest and most flexible wrapper of its kind.

Color touchscreen controls on a swivel panel, easily accessible and intuitive to use. Easy-access sliding doors that completely lift out, easy-mount-easy-thread film carriage, and Generation 3 servo drives that eliminate the need for air simplify operation and maintenance.

OSS-205 & OSS-209

Texwrap OSS-205 and OSS-209 continuous motion orbital side sealers are designed for bakery applications demanding the highest production rates.

Designed for the special requirements of a food production environment, the OSS-205 and OSS-209 corrosion resistant design features stainless steel construction and a removable washdown infeed.

When combined with the correct infeed system, OSS-205 and OSS-209 side sealers are capable of packaging speeds up to 250 per minute. Texwrap offers many types of infeeds designed to handle a variety of bakery items from pizza to cakes and pies. Each product has very specific handling demands in order to run at high speed without damage.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of OSS Side Sealers

	OSS-145	OSS-205	OSS-289	OSS-209
Max Package Size	4"H x 14"WInfinite length	4"H x 20"WInfinite length	8"H x 28"WInfinite length	8"H x 20"WInfinite length
Max Film Width	24" Center fold48" Single wound	27" Center fold54" Single wound	36" Center fold72" Single wound	27" Center fold54" Single wound
Conveyor Speed	Up to 200 feet per minute		Up to 250 feet per minute	
Footprint	118"L x 70"W	120"L x 85"W	146"L x 95"W	137"L x 81"W
Construction	Heavy-duty welded tubular steel standard. Optional corrosion resistant design.			
Orientation	Right or left hand configuration			

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.