



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Starview SP-IR Semi-Auto Retractable Heat Skin Packaging Machine



At a Glance

- Designed for low to medium volume applications
- SP models have a stationary heating system with instant on/off heaters
- SP-IR models incorporate an automatic retractable radiant heater panel system
- PLC timer control for precision repeatability

Buy your [skin packaging materials](#) from us, and get a discount on this Starview skin packager!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Medium Volume Retractable Heat Skin Packaging Machines

Starview SP and SP-IR Series skin packaging machines are designed for low to medium volume applications. SP machines incorporate a stationary heating system with instant on/off heaters. SP-IR models incorporate an automatic retractable radiant heater panel system, controlled by percentage controllers for precise heat distribution.

All SP and SP-IR skin packaging machines have PLC timer control for precision repeatability and an accurate turbine regulator. An infeed table, out-feed table and impulse type hot wire cut-off are all standard.

These skin packaging machines can be equipped with a three-stage vacuum system for products with complex shapes. The SP-IR series may be ordered with a blister forming option to produce low-profile blisters from roll stock.

Features of the SP and SP-IR Series

Standard sizes 18" x 24" through 36" x 48" offered
Use for retail carded packaging or shipping containment
PLC machine control with touch screen operator interface panel
Infeed and outfeed tables standard
Impulse hot wire cut-off standard
Heavy-duty industrial design for long life

Please [contact Pro Pac](#) or call 888-318-0083 for your skin packaging equipment.

Specifications of the SP-IR Skin Packaging Machines

Specifications	SP-IR-1824	SP-IR-2430	SP-IR-2436	SP-IR-3036
Max Card Size	18" x 24"	24" x 30"	24" x 36"	30" x 36"
Max Product Height	10"	10"	10"	10"
Heating System	Radiant panel	Radiant panel	Radiant panel	Radiant panel
Light Curtain	Standard	Standard	Standard	Standard
Average Cycle	15 - 45 seconds	15 - 45 seconds	15 - 45 seconds	15 - 45 seconds
Electrical	208-230V, 3 ph, 50 amps	208-230V, 3 ph, 55 amps	208-230V, 3 ph, 70 amps	208-230V, 3 ph, 80 amps

Specifications of the SP Skin Packaging Machines

Specifications	SP-1824	SP-2430	SP-2436	SP-2448
Max Card Size	18" x 24"	24" x 30"	24" x 36"	24" x 48"
Max Product Height	10"	10"	10"	10"
Heating System	Quartz impulse	Quartz impulse	Quartz impulse	Quartz impulse
Light Curtain	Optional	Optional	Optional	Standard
Average Cycle	15 - 60 seconds	15 - 60 seconds	15 - 60 seconds	15 - 60 seconds
Electrical	208-240V, 3 ph, 32 amps	208-240V, 3 ph, 55 amps	208-240V, 3 ph, 70 amps	208-240V, 3 ph, 100 amps

Specifications	SP-3036	SP-3048	SP-3648
Max Card Size	30" x 36"	30" x 48"	36" x 48"
Max Product Height	10"	10"	10"
Heating System	Quartz impulse	Quartz impulse	Quartz impulse
Light Curtain	Standard	Standard	Standard
Average Cycle	15 - 60 seconds	15 - 60 seconds	15 - 60 seconds
Electrical	208-240V, 3 ph, 80 amps	208-240V, 3 ph, 90 amps	208-240V, 3 ph, 100 amps

Please [contact Pro Pac](#) or call 888-318-0083 for your skin packaging equipment.