



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Dynaric AM659A Fully-Automatic Strapper



## At a Glance

- Fully-automatic strapper utilizing the latest servo motor technology
- Applies up to 25 bundles per minute
- Full-color touch-screen controls with diagnostics
- Externally located dispenser

Buy your [strapping material](#) from us, and get a discount on this Dynaric strapping equipment!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Fully Automatic Strapping Machine Provides the Ultimate in Reliability

Incorporating the latest servo motor technology, the Dynaric AM659A uses less energy to operate and greatly reduces the number of moving parts. Machine maintenance is minimized, delivering a quicker return on investment.

Because of its ability to use various sizes of plastic strap, the AM659A enables you to choose the most cost-effective plastic strap for your packaging process.

To ensure performance and ease of operation for the equipment operator, the AM659A offers many standard features that include automatic coil feed system, strap loop ejector, short feed detector, refeed system and push button or automatic strap cycle.

## Features

Fully-automatic strapping machine, designed to be used with Dynaric polypropylene strap

Up to 25 bundles per minute

Reliable AC servo motors and drives

Direct access controls for quick adjustments

Four tier LED status light tower

Automatic strap feed

Strap width 5mm - 12mm

Exclusive eject function avoids strap jam

Torque controlled strap tension, adjustable

Upstream and downstream interlocks

Conveyor speed steplessly adjustable  
Straightforward operator interface  
Easy machine mobility  
Bundle press, optional

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

## Specifications of the AM650A

Overall Width	24.0" (610mm)
Overall Length	57.0" (1450mm)
Overall Height	59.1" (1448mm)
Weight	617 lbs (280 kg)
Cycle Time	2.4 seconds
Cycle Initiation	Photo eye or push button
Strap Size	3/8" - 1/2" (9mm - 12mm) (optional 5 - 6mm)
Sealing Method	Heat seal
Sealing Head Location	Bottom: 17.5" (444.5mm) from right side of the machine
Strap Tension	Externally located, touch pad adjustable 6.6 - 132 lbs
Package Size	Min 4.72"W x 1.57"H x 4.72"L Max depending on arch size
Power	110/230 Volt AC (460 Volt AC)
Mobility	2 swivel and 2 fixed casters
Dispenser	Externally located 8" or 9" I.D. / 8" or 9" Face / 18" O.D.