



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Dynaric AM659YSSA Side Seal Automatic Stainless Steel Strapper



At a Glance

- Fully automatic stainless steel strapper for meat, poultry, and seafood industries
- Side seal automatic strapping machine constructed around a solid, heavy duty frame
- Servo motors for precise performance
- 50 strapping cycles per minute

Buy your [strapping material](#) from us, and get a discount on this Dynaric strapping equipment!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Side Seal Strapping for the Meat, Poultry, Seafood, and Agricultural Industries

From the inside-out, the Dynaric AM659YSSA stainless steel side seal banding machine is designed to handle the increasing production the food, fruit and vegetable industries are seeing today.

To withstand the industrial conditions this high-speed side seal fully automatic food packaging strapper is constructed around a solid, heavy duty frame and stainless steel body panels.

The stainless steel body panels are easily cleanable and are corrosion resistant. The AM659YSSA banding machine uses the latest servo motor technology to maintain peak performance throughout its many years of service. This food package strapper can literally be adapted to your application whether you need special features, options or a modification. See why this machine is quickly becoming the most used strapper in the industry.

Features

- Servo motors for optimum performance
- Increased machine reliability by eliminating belts, clutches and pulleys
- Wide range electronic tension control
- Adjustable strap heat seal/dwell time for optimum seal joint efficiency
- Applies 50 straps per minute
- Operator friendly automatic coil feed system for ease of start up
- End of strap sensor and strap loop ejector
- Strap re-feed system in case of a short feed

Standard equipped with photo sensors for fully automatic operation
Multiple arch sizes available to meet your packaging requirements

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

Specifications of the AM659YSSA

Cycle Time	50 straps per minute
Tension Range	2.2 - 121 lbs
Strap Width	9mm or 12mm
Sealing Method	Heating element
Reel Inside Diameter	200, 230, 280 mm
Power Supply	110/220/230/240V,50/60Hz,1PH
Power Consumption	0.7 kw
Standard Arch Size	600mmW x 600mmH
Layout Dimension	2070mmL x 580mmW x 1425mmH
Table Height	695mm
Machine Weight	640 lbs