



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Greenbridge PC1000SP Automatic Strapping Machine



## At a Glance

- Cycle speed up to 65 straps per minute
- Straps packages as small as 1.7W x 0.375H
- No belt, clutches, or pulleys
- German DC brushless stepper motor technology

Buy your [strapping material](#) from us, and get a discount on this Polychem strapping equipment!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Fast Automatic Small Package Strapping Machine

The innovative high-speed automatic Greenbridge PC1000SP small package strapping machine is capable of strapping packages as small as 1.7" wide x 3/8" high. Equipped with all industry standard features, the PC1000SP offers optimal performance, high cycle speed, and easy maintenance.

## Features

- Cycle speed is up to 65 straps per minute (depending on arch size)
- German DC brushless motor technology
- No belt, clutches, or pulleys
- 30% fewer parts equals less maintenance
- Waist high quick-change coil and strap feed
- Easy access operating control panel
- Easy access strap chute, no tools required
- Front foot-bar pedal plus moveable foot switch
- One piece strap chute
- Sensor controlled heater
- End of coil strap ejector / loop ejector
- Electronic brake / auto loader
- Adjustable table height 32" to 36"
- Arch size 21" x 16"

## Options

Photo-eye activation

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

## Specifications of the PC1000SP

Cycle Rate	Up to 65 straps per minute (depending on arch and package size)
Maximum Package Weight	100 lbs
Table Height	32" to 36"
Strap Tension	Up to 100 lbs
Strapping Material	Polypropylene: 3/8", 5mm, 6mm, 9mm
Electrical Requirements	110V, 60Hz 1PH
Machine Weight	450 lbs