



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Greenbridge PC1000SS Automatic Strapping Machine



At a Glance

- Cycle speed up to 65 straps per minute
- All SUS 304 stainless steel
- No belt, clutches, or pulleys
- German DC brushless stepper motor technology

Buy your [strapping material](#) from us, and get a discount on this Polychem strapping equipment!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast Automatic Stainless Steel Strapping Machine

The innovative high-speed automatic Greenbridge PC1000SS strapping machine is built with SUS 304 stainless steel. Made for the harsh environments of the meat, poultry, and fish industries, the PC1000SS is equipped with all industry standard features. The PC1000SS offers optimal performance, high cycle speed, and easy maintenance.

Features

- All SUS 304 stainless steel
- Cycle speed is up to 65 straps per minute (depending on arch size)
- German DC brushless motor technology
- No belts, clutches or pulleys
- 30% fewer parts, less maintenance
- Waist high quick change coil and strap feed
- Easy access operating control panel
- Easy access strap chute-no tools required
- Front foot-bar pedal plus moveable foot switch
- One piece strap chute
- Sensor controlled heater
- End of coil strap ejector / loop ejector
- Electronic brake / Auto loader
- Adjustable table height from 32" to 36"
- Lockable casters

Arch sizes 25"W x 19"H and 33"W x 23"H, others are special order
Roller top standard on arches 33" wide or wider

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

Specifications of the PC1000SS

Cycle Rate	Up to 65 straps per minute (depending on arch and package size)
Arch Sizes	25"W x 19"H to 65"W x 19"H
Maximum Package Weight	100 lbs
Table Height	32" to 36"
Strap Tension	Up to 100 lbs
Strapping Material	Polypropylene: 3/8", 5mm, 6mm, 9mm, 12mm
Electrical Requirements	110V, 60Hz 1PH
Machine Weight	450 lbs