



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Greenbridge PC1500SS Automatic Strapping Machine



At a Glance

- Cycle speed up to 60 straps per minute
- Side seal configuration
- Smart LCD display
- German DC brushless stepper motor technology

Buy your [strapping material](#) from us, and get a discount on this Greenbridge strapping equipment!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Stainless Steel Side Seal Automatic Strapping Machine

The Greenbridge PC1500SS side seal strapping machine is built with 304 stainless steel and is IP54 rated. The side mounting prevents debris from contaminating the seal head. Made for the harsh environments of the meat, poultry, and fish industries, the PC1500SS is equipped with all industry standard features.

Features

Side seal configuration
Cycle speed up to 60 straps per minute (depending on arch size)
304 stainless steel
IP54 rated splash down machine
End of cycle and strapping error signals
Various arch sizes
Internal strap dispenser protects strap from water
Water resistant design

Options

Press size pusher
Operator friendly triple lamp low strap sensor
End of cycle and strapping error signals
Pneumatic vertical press bar
Energy saving conveyor with auto sleep mode (PC)
Available without adjustable roller table

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

Specifications of the PC1500SS

Cycle Rate	Up to 60 straps per minute
Minimum Package Size	4"W x 4"H
Maximum Package Weight	100 lbs
Stock Arch Sizes	33" x 23", 41" x 31", 65" x 39"
Table Height	32" to 36"
Strap Tension	Up to 120 lbs
Strapping Material	Polypropylene: 1/4", 3/8", 1/2", 5mm, 6mm, 9mm, 12mm
Core Size	8" x 8"
Electrical Requirements	110V, 220V, 50/60Hz, 1 Phase
Machine Weight	800 lbs