



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Greenbridge PC2000CX Fully-Automatic Strapping Machine



## At a Glance

- Stainless steel, fully-automatic strapping machine for the meat, poultry, and seafood markets
- Up to 65 bundles per minute
- German DC brushless motors reduced maintenance costs with fewer parts

Buy your [strapping material](#) from us, and get a discount on this Greenbridge strapping equipment!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Fast Fully-Automatic Stainless Steel Strapping Machine

The Greenbridge PC2000CX stainless steel, fully-automatic strapping machine is designed for the meat, poultry, and seafood markets. This strapping machine is capable of up to 65 straps per minute. Production bottle necks are virtually eliminated with this high rate of throughput.

## Features

- Robust and compact strapping head
- Standard arch size 25" W x 19" H
- Free access to strap guides (patents registered)
- Electronic tension control / auto strap ejector
- Dual photo eyes/ Siemens PLC control
- Hinged top plates (7 gauge) / splash guard over seal head
- Dual cylinder pneumatic press for agility and finely tuned package compression
- Pneumatic air gun for easy maintenance cleaning
- Extra wide HD locking castors to handle quick movements in and out of station
- Fixed strap cutter near strap coil for convenience
- Multiple strap function for single, double, continuous or transit mode
- Belt-driven table with variable conveyor speed between 10 and 60 meter/min
- Up and down stream interlock with complete plug connection
- Easy reversible package flow
- Loop ejector

## Options

Operator friendly triple lamp low strap sensor

Extension belt-driven table of 8 inches on upstream and downstream side

Lower adjustable table 35.5 inches

Additional internal parts available for 304 stainless

Energy saving transmit with auto sleep mode

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

## Specifications of the PC2000CX

Cycle Rate	Up to 65 bundles per minute depending on arch and package size
Strap Feed	Fully automatic
Arch Size	25"W x 19"H
Max Package Weight	100 lbs
Strap Tension	115 lbs (9mm)
Strapping Material	Polypropylene: 5mm, 6mm, 9mm, 3/8", 1/2"
Electrical Requirements	110V, 60 Hz, 1 phase
Machine Weight	450 lbs