



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Wulftec VarioMaster 9440 Strapping System



At a Glance

- Specifically designed for corrugated boxes and pallet loads
- Strapping head is side-mounted on the arch and movable
- Standard undertrack style of strapping arch bottom
- Or an electric motor driven pallet bayonet for through-pallet strapping, or a combination of both

Buy your [strapping material](#) from us, and get a discount on this Wulftec strapping equipment!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

High-Performance Strapper for Boxes or Pallet Loads

High-performance side seal strapping machine for boxes or pallet loads. Can be integrated into conveyor line. Strapping head is side mounted on the arch and movable. During the strapping cycle, the strapping head indexes towards the load before tensioning sequence, so tensioning and sealing are done right against the side of the load. The bottom section of the strapping arch can be a standard undertrack style, or an electric motor driven pallet bayonet for "through-pallet" strapping, or a combination of both.

Features

AC variable frequency drives are standard equipment on all machines

Lower maintenance and better reliability

Wulftec stretch wrappers will save time and money

NEMA 4/12 control panel dust tight and waterproof

Control panel is neatly organized eliminating time otherwise lost searching for wires

Control panel is UL508A approved

Superior electrical design including Allen Bradley MicroLogix PLC and AC drives

User-friendly touch-screen offers a simple yet effective way to adjust and maintain your equipment

All motors, proximity sensors, photoeyes and other sensors have quick disconnect cables that simplify installation and maintenance

Photoeyes are maintenance free and protected

All Wulftec structures are made of heavy-duty steel for rugged performance, even in the harshest work environments

Wulftec machines are built to last forever

During the strapping cycle, the strapping head indexes towards the load before tensioning sequence, so

tensioning and sealing are done against the side of the load.

The strapping head is mounted on a movable assembly guided through linear bearings, and activated by an electric motor with a timing belt. The head has a load sensing device that detects the side of the load and tells the head movement to stop so tensioning and welding are done as close as possible to the product for maximum strap containment efficiency.

The bottom section of the strapping arch can be a standard undertrack style or an electric motor driven pallet bayonet for "through-pallet" strapping or a combination of both.

Up to 8 straps per minute may be applied, depending on strapping arch and package dimensions, strap quality and strap tension required

PET or polypropylene strap may be used with minor adjustments to the strapping head

Electronic tension control through a variable frequency drive. Assures consistent tension control regardless of the number of cycles and environmental conditions.

Strap tension is adjustable from the touch screen.

The VarioMaster 9440 offer turntables, rotating cross and centering devices as an option for all handling needs, accommodating pallet and palletless loads.

Wulftec heavy-duty conveyors are second-to-none in the industry

Coils of PET or polypropylene strapping with a core diameter of 16" can be fitted to the high speed dispensers, with pulley block accumulation system and electrical brake.

Ability to strap with polyester or polypropylene strapping without parts changes

Non-Proprietary parts accessible on a local base

Best Warranties in the Industry

1-year on the strapping head and track

3-year unlimited cycle warranty

3-years on the steel structure

Please [contact Pro Pac](#) or call 888-318-0083 for your strapping equipment.

Specifications of the VarioMaster 9440 Strapping System

Production Rate	100 loads per hour
Dimensions	205" L x 35" W x 85" H
Approximate Shipping Weight	1100 lbs
Maximum Load Size	60"W x 80"H
Maximum Load Weight	Limited to conveyor capacity
Electrical Requirements	460 V /3 ph /60Hz 15A
Controls	Allen Bradley MicroLogix 1200 PLC 24V control system NEMA 4/12 control cabinet Power on/off lockable switch and indicator light Manual function for strapping head Strap track with under track configuration to allowing under pack strapping 2 communications I/O signals with upstream & downstream system Allen Bradley series 100 contactor
GS41 HT Strapping Head	By changing the optional entry and exit guide the head have the ability to strap with polyester (PET) from 3/8 to 5/8 wide and .020 minimum thick strapping (Special adjustment required for PP, consult us) Consistently reproducible strap tensioning through an Allen Bradley PowerFlex 70 VFD and torque motor control Consistently high seal efficiency Environmentally favorable sealing by vibration welding Separate drive section for high speed strap feeding and take up and to achieve maximum tension levels Electronic strap circulation control
Strap Dispenser	High-speed dispenser with pulley block accumulation system and electrical brake that can fits standard coils of PET/PP strapping with a core diameter of 16" and a width of 6"
Structure	Heavy duty folded sheet metal uprights with upper frame structurally integrated with base for greater stability
Technical Information	The machine is provided with a manual including electro/mechanical schematics and drawings, maintenance program and PLC program disk