



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Orion RTD Semi-Auto Rotary Arm Stretch Wrapper



At a Glance

- Designed for wrapping difficult, extremely heavy, light, fragile and unstable loads
- Structural steel construction for durability and security
- No maximum load weight capacity

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Wrap Pallet Loads on the Floor, without Turning the Load

Built for safety, dependability, the Orion RTD semi-automatic stretch wrapper models represent the latest in rotary tower stretch packaging technology. Because the RT model stretch wrappers rotate the film carriage around a stationary load, they are ideal for unitizing even the most difficult loads, including those that are extremely heavy, light, fragile or unstable. Rotary arm stretch wrapper systems wrap load on the facility floor, and can be loaded by pallet jack or lift truck.

This RTD stretch wrapper has no maximum load weight capacity. For ease of motion, this pallet wrapper has a precision ring bearing drive system and a tower mounted obstacle sensing system. Orion RTD stretch wrappers have a structural steel construction for durability and security.

Orion RTD stretch wrappers ensure high performance with a film delivery carriage, as well as the AC/VFD motors, which reduce maintenance.

Features

- 16 RPM variable speed tower
- No maximum load weight capacity
- High performance film delivery carriage
- 7" IntelVue color HD touch screen HMI
- Multiple wrap recipes can be programmed
- Certain programmed functions can be locked

Precision ring bearing tower support
Optional Insta-Cut severs film web
AC/VFD motors for reduced maintenance
Structural steel construction for durability
Heavy-duty chain & sprocket drive
Tower-mounted obstacle sensing system
Up to 40 loads per hour
Based on 80" tall load, 12 revolutions
Maximum load 52"W x 52"L x 80"H (74" Diagonal)
InstaThread film delivery system
Film roll: 20" Standard, 30" Optional, 10" Diameter
Standard prestretch ratio: 260% (higher available)
Ultra low wrap to within 1.5" of floor
Automatic load height sensing photoeye
Automatic film force-to-load control
SHIPPING WEIGHT 2,500+ lbs. (Varies with options)
Warranty: 4 years on all major components, 5 years on structural frame
115/1/60, 20 Amp electrical service

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.