



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Robopac Genesis Futura XL Automatic Rotary Ring Stretch Wrapper



## At a Glance

- 30 RPM for reliable, consistent wrapping
- Up to 60 loads per hour
- Built to handle extra-large pallet loads
- Rotary ring for smooth, high-speed operation
- Patented no-contact power system for reduced maintenance

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Rotary Ring Stretch Wrapper for Extra-Large Pallet Loads

The Robopac Genesis Futura XL automatic rotary ring stretch wrapper is built to handle extra-large pallet loads with precision, speed, and reliability. Designed for high-volume operations, the Futura XL stretch wrapper features an oversized ring that accommodates pallet sizes up to 75" x 75", making it ideal for bulky or irregular loads.

Sixteen standard wrapping recipes allow operators to easily select and consistently repeat the best wrapping pattern for pallet loads in less time.

With a 30 RPM ring speed and a throughput capacity of up to 60 pallet loads per hour, the Genesis Futura XL delivers performance without compromise.

## Features

**Allen Bradley Panel View Plus 600**

**Automatic Film Cut**

**Cube Smart Stretch Wrapping Technology** Innovative technology that combines multi-level variable pre-stretch, multi-level variable containment force, pro-active corner compensation, and strategic film placement to successfully wrap loads & ensure that they reach your customer in as-made condition by maintaining proper wrapping standards.

**Multi-Level Variable Containment Force** Delivers optimal containment force at each level. Containment force is adjustable up to 9 times on each load.

**Multi-Level Variable Pre- Stretch** Ensures the best film economy for every load. Adjust the pre-stretch up to 9 times on each load. Multi-Level Variable Pre-Stretch Technology delivers 30% to 55% film savings over currently available competitive stretch wrapping systems.

**R-Connect Ready** Able to install R-Connect remote monitoring software immediately.

**Split Wrapping Cycles for Stacked Pallets**

## Robopac ECube Technology

Deliver exactly the right amount of film at exactly the right position with exactly the right containment force.

- Reduces film cost by 30% to 55%
- Improves load containment
- Reduces product damage by 40%

**Multi-Level Variable Pre-Stretch**

- Ensures best film economy for all loads
- Ensures best film economy for all films
- Ensures highest containment level attainable for all films
- Delivers 30% to 55% film savings

**Multi-Level Variable Containment Force**

- Delivers the optimal containment force at each level
- Enables the delivery of the highest pre-stretch at all levels

**Strategic Film Placement**

- Scientific approach to ultimate load containment
- Place film precisely where it has the most impact on load containment

**Proactive Corner Compensation**

- Reduces product damage on corners
- Improves containment on flat sides of loads
- Enables higher containment levels on each revolution

## Automatic Roll Change

Patented motorized unit automatically changes film roll without operator assistance, expelling the empty roll core, and replacing it with a full roll.

Single ARC/1 and double ARC/2 versions are available in the pallet top covering system. The ARC/2 solution houses two full rolls providing the operator with greater roll change flexibility.

Roll change units are installed within the perimeter guards but outside the ring work range. Therefore, new rolls can be installed safely without stopping stretch wrapping operations.

## Ring Lift

Two-chain interconnected ring kinematics ensure synchronous ring lift. Supported by a robust 4-column structure combined with an upper sheet metal frame creates maximum safety conditions, even in the most heavy duty conditions. Ring lift and lowering speeds are adjusted by frequency converter from the control panel.

## Rotation Unit

Rotating ring planarity and dimensional constancy are guaranteed to work at maximum speed, and to protect the integrity and working life of parts in motion. Drive is created by a high-resistance, reliable, and silent belt. Rotation speed is controlled by a frequency converter, continuously regulated by the control panel.

## Pre-Stretch Carriages

**BSCSP Carriage** Single motor on-board carriage automatically recharges batteries to pre-stretch film from the beginning of the wrapping process. Pre-stretch film at fixed values up to 300%. Adjustment of containment force on the pallet is reactive and controlled by an analog system.

## Stretch Wrapper Clamps

**Futura Clamp** Pneumatically driven clamp with hot wire cuts and seals the film tail.

**Nip and Tuck Clamps**, cuts and threads film without a sealer. The last tail of film is inserted into the winding itself.

## Options

**Vertical Pressure Platen** Pallet retaining system during wrapping used with upper covering systems (top inside / top outside) or with particularly unstable loads. Available with mechanical movement of pantograph system or pneumatic drive.

**Pallet Lifter** Pallet lifting system in the center of the conveyor with pneumatic or hydraulic drive allows complete wrapping of the wooden pallet. This system manages wrapping of the product and pallet in a flexible manner, guaranteeing maximum stability of the palletized load. The pneumatic lift has a maximum capacity of 4400 lbs. The hydraulic system has a capacity of more than 4400 lbs.

**Top Cover** Automatic system for covering the upper surface of the pallet load. Top Inside version is integrated in the structure of the machine provides a cover against dust and water. Top Outside version with independent structure provides a dust-proof cover.

**Roping** Roping system reduces the width of film to a cord and ensures a more effective stabilization of the load.

**VCA Corner Applicator** Gripping and application devices automatically locate the four corners of the pallet load without any manual setting or adjustment of the system.

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

## Specifications

Pre-Stretch Carriage	BSCSP
Pre-Stretch Ratio	140% - 180% - 220%
Power	380 - 400 - 415 V, 50 Hz
Air	6 +/- 1 bar, 250 - 350 NL / min

## Throughput & Pallet Sizes

Helix Wrapper	Futura 40	Futura 40 TI	Futura L	Futura L TI	Futura XL	Futura XL TI
Pallets per Hour	80 pph	70 pph	65 pph	55 pph	60 pph	50 pph
Min Pallet Dimensions	20" x 24", 500 x 600 mm		24" x 24", 600 x 600 mm		24" x 24", 600 x 600 mm	
Max Pallet Dimensions	44" x 52", 1100 x 1300 mm		58" x 58", 1450 x 1450 mm		76" x 76", 1900 x 1900 mm	

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.