



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Robopac LT Automatic Turntable Stretch Wrapper



At a Glance

- 17 RPM
- Up to 35 loads per hour
- 5 foot infeed & outfeed conveyors
- Variable turntable & carriage speeds
- 10 inch color touchscreen
- Safety fencing

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Entry-Level Automation, High-Level Performance Stretch Wrapper

The Robopac LT automatic stretch wrapper is designed to bring reliable automation to low to medium volume operations. With a fast 17 RPM turntable and a footprint that fits almost anywhere, this Robopac LT stretch wrapper wraps pallets quicker, safer, and using less film. Boost productivity without overcomplicating workflow.

Benefits

- Fast & Efficient – Wrap at up to 17 RPM with consistent, secure results
- Compact Footprint – Fits into tight spaces without sacrificing performance
- Safe by Design – Automatic operation with full safety fencing to protect your team
- Cost-Effective – Reduce film usage and labor without the price tag of a high-volume system

Key Features

- 10" Color Touchscreen – Intuitive control with real-time system feedback
- Allen Bradley PLC & Drives – Trusted reliability and precision performance
- 15 Custom Wrap Recipes – Powered by Cube Technology for smart film application
- Variable Turntable & Carriage Speeds – Fine tune wrap cycles to match your product
- Automatic Load Height Sensing – Ensures complete coverage every time
- Automatic Film Tail Treatment – Clamp, cut, and wipe for a clean finish

- 5' Infeed & Outfeed Conveyors – Streamlined flow of pallets through your line
- Adjustable Conveyor Pass Heights – 18" to 24" for flexible integration
- Safety Fencing – Keeps operators protected during operation

Feature Details

Control Panel Includes Allen Bradley Micro 800 series PLC. The 10 inch control panel with color touch screen makes this Robopac stretch wrapper easy to program and operate. Includes 15 customizable wrap recipes with Cube Technology.

Automatic Load Height Sensing Automatically senses top of load to provide the load with full film coverage.

Automatic Film Tail Treatment Cut, clamp, and wipe down unit secures the film tail at the end of the wrap cycle to the load to avoid loss of containment at the bottom of the load.

Small Footprint With one of the smallest footprints in its category, the Robopac LT automatic stretch wrapper is able to be placed in areas that meet operations workflow requirements.

Safety The Robopac LT automatic stretch wrapper includes industry standard safety fencing and photo eyes. Additional category 3 safety devices can be added to this stretch wrapping system.

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

Specifications

Performance

Production Speed 30-35 LPH

Rotation Speed 17 RPM

Load Capacity

Max Load Weight 4000 lbs

Max Load Dimensions 52" x 52" x 82"

Min Load Dimensions 36" x 36" x 18"

Load Handling

Turntable Speed 7 - 17 RPM

Turntable Diameter 69"

Conveyor 40/60 FPM, 52" width, adjustable 18 - 24" pass height

Film Delivery

Pre-Stretch Fixed 200%, Optional 150%, 250%, 300%

Roll Dimension 10" diameter, 20" width

Utilities

Electrical 480V, 20Amp, 60Hz, 3Ph

Air Pressure 3 CFM, 80 PSI

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.