



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Robopac Semi-Auto Compacta Tire Horizontal Stretch Wrapper



At a Glance

- Wrap motorcycle, ATV, go-kart, and lawnmower tires up to 33 inches in diameter
- Max rotation speed: 70 RPM
- Power guides position and rotate tires during wrapping

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast, Reliable Tire Wrapping for Powersports and Lawn Equipment

Robopac Compacta tire horizontal stretch wrappers are purpose-built to wrap motorcycle, ATV, go-kart, and lawnmower tires up to 33" in diameter. Eliminate the need for bulky, expensive corrugated packaging.

Vertical power guides position and rotate tires during wrapping. A color touchscreen control panel capable of running pre-set programs. Safe, simple operation includes automatic film clamping, cutting and heat sealing unit.

All Robopac Compacta Ring Wrappers Feature constant film tensioning to improve package integrity and reduce film breaks. Are equipped with safety options that adhere to rigorous CE safety standards.

Features

Wraps Tires Up to 33" in Diameter Ideal for motorcycle, ATV, and outdoor equipment tires.

Self-Centering Guides Centers product in the ring and automatically rotates product to provide a smooth, contiguous tire wrap—suitable for shipping.

Touchscreen Control Panel Intuitive 7" color touchscreen control panel provides quick and easy access to operating the turntable wrapping machine for tires. Up to 20 custom programs can be stored and recalled.

Automatic Film Clamp, Cut, and Heat-Seal Cuts film after wrapping and seals the film tail to the product.

Consistent Film Tensioning Reduces film breaks and improves package stability.

Corrugated-Free Packaging Cut costs and waste by switching to stretch film.

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

Specifications

Belt Driven	Yes
Fully Auto Wrap Cycle	Yes
Constant Film Tensioning	Yes
Max Ring Speed	75 RPM
Film Width	5"
Max Film Roll Diameter	8"
Film Core	3"
Power	480V, 3 ph, 50/60 Hz
Air	6 bar

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.