



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Robopac 708 Semi-Auto Rotary Arm Stretch Wrapper



## At a Glance

- 12 RPM for reliable, consistent wrapping
- Up to 35 loads per hour
- Ideal for unstable or heavy pallet loads
- Simple-to-use 7 inch touch screen

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Rotary Arm Stretch Wrapper for Heavy and Unstable Loads

The Robopac Rotary 708 stretch wrapper is engineered for high-performance wrapping of heavy, unstable, or irregular loads. With CUBE Technology and an intuitive interface, the Rotary 708 stretch wrapper delivers precision control, film savings, and optimal load containment.

Built for demanding environments, the Rotary 708 helps increase packaging speed, cut costs, and ensure every load is delivered in as-made condition.

## Benefits

**Cube Technology** Cut film usage by 30% to 55%, improve stability, and reduce damage

**Patented Roll Carriage Design** Flexible enough to wrap any load with any film

**Advanced Control** Adjust containment force, speed, roping, and banding at 9 customizable points per load

## Features

**R-Connect** R-Connect provides usage and performance data via the cloud. Meet Industry 4.0 demands with performance monitoring and optimization at your fingertips. R-Connect empowers you with actionable insight to promptly investigate alarms, adjust parameters, improve performance, reduce down time.

**7" Color Touch Screen** With a large 7" simple-to-use color touch screen, simply set up correct parameters for wrapping each load. Record up to 12 different programs (6+6 with multi-level control).

**PVS Carriage** Powered stretch system is controlled by two independent motors. From the panel board, adjust stretch ratio from 150% to 400%, and control force-to-load with patented electronic device.

**Adjustable, Extendable Rotating Arm** A robust structure made of 0.25 inch steel forms the backbone of this powerful rotating horizontal rotary arm wrapper. Adjust the length of the rotating arm to wrap pallet loads up to 55" x 55", or down to a pallet load size of 16" x 16".

### Film Delivery System

- Power variable stretch: 150% – 400%
- Containment force: Load cell
- Film carriage motor: 1/3 HP VAC
- Height sensing: Automatic photo eye
- Film threading: Patented S pattern
- Corner compensation: Load cell
- Standard film width: 20" (30" option)

### Safety Features

- Safety bumper warning light
- Safety alarm
- CE Compliant, UL, CUL

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

## Specifications

Production Speed	Up to 35 loads per hour
Wrap Arm Speed	12 RPM
Rotary Arm Drive	1 hp VAC
Remote Control	Standard
Max Pallet Dimensions	55" x 55" x 78"
Max Pallet Weight	Unlimited
Power	120V, 13.2 amp, 60 Hz, 1 PH

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.