



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Robopac 708 CS Semi-Auto Rotary Arm Stretch Wrapper



## At a Glance

- 12 RPM for reliable, consistent wrapping
- Up to 35 loads per hour
- Cut, clamp, and spread system keeps operators on the forklift.
- Ideal for unstable or heavy pallet loads
- Simple-to-use 7 inch touch screen

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Rotary Arm Stretch Wrapper with Cut & Spread System

The Robopac Rotary 708 CS semi-automatic rotary arm stretch wrapper is designed to handle challenging loads with maximum efficiency. Equipped with a cut, clamp, and spread (CS) system, this machine allows operators to stay on the forklift.

From cost savings to product protection, the Rototech 708 CS stretch wrapper is a smart investment for packaging lines focused on speed, safety, and material efficiency.

## Benefits

**Built for Heavy & Unstable Loads** No pallet rotation

**Automatic Cut, Clamp & Spread System** Saves up to 30 seconds per load

**CUBE Technology** Reduce film use by 30% to 55%, improve load containment, and lower product damage

**Forklift Friendly** Keeps operators in the truck for faster cycles and improved safety

**Reliable Rotary Arm Design** Built for consistent, high-performance wrapping

**Touchscreen Control** Easy parameter setup with load-specific adjustments

## Features

**Automatic Film Cut, Clamp & Spread System** The Robopac cut, clamp and spreading system ensures perfect adherence of the final round of film on the wrapped product. The aluminum clamp, controlled by a pneumatic cylinder, holds the film without slippage during cutting.

**R-Connect** R-Connect provides usage and performance data via the cloud. Meet Industry 4.0 demands with performance monitoring and optimization at your fingertips. R-Connect empowers you with actionable insight to promptly investigate alarms, adjust parameters, improve performance, reduce down time.

**7" Color Touch Screen** With a large 7" simple-to-use color touch screen, simply set up correct parameters for wrapping each load. Record up to 12 different programs (6+6 with multi-level control).

**PVS Carriage** Powered stretch system is controlled by two independent motors. From the panel board, adjust stretch ratio from 150% to 400%, and control force-to-load with patented electronic device.

**Adjustable, Extendable Rotating Arm** A robust structure made of 0.25 inch steel forms the backbone of this powerful rotating horizontal rotary arm wrapper. Adjust the length of the rotating arm to wrap pallet loads up to 55" x 55", or down to a pallet load size of 16" x 16".

### Film Delivery System

- Power variable stretch: 150% – 400%
- Containment force: Load cell
- Film carriage motor: 1/3 HP VAC
- Height sensing: Automatic photo eye
- Film threading: Patented S pattern
- Corner compensation: Load cell
- Standard film width: 20" (30" option)

### Safety Features

- Safety bumper warning light
- Safety alarm
- CE Compliant, UL, CUL

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

## Specifications

Production Speed	Up to 35 loads per hour
Wrap Arm Speed	12 RPM
Rotary Arm Drive	1 hp VAC
Max Pallet Dimensions	55" x 55" x 78"
Max Pallet Weight	Unlimited
Power	115V, 20 amp, 60 Hz, 1 PH
Air	90 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.