



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Robopac HD XL Semi-Auto Rotary Arm Stretch Wrapper



At a Glance

- 11 RPM for reliable, consistent wrapping
- Up to 25 loads per hour
- Built for heavy and unstable loads.
- Ideal for unstable or heavy pallet loads
- Simple-to-use 3.5 inch touch screen

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Rotary Arm Stretch Wrapper for Heavy, Unstable Loads

The Robopac Masterwrap HD XL semi-automatic rotary arm stretch wrapping machine is built for heavy and unstable loads. The Masterwrap HD XL combines powerful pre-stretch film delivery, easy-to-use controls, and R-Connect remote monitoring to give your stretch wrapping operation a cost-effective and consistent packaging solution.

The Robopac Masterwrap HD XL stretch wrapper helps you optimize your packaging workflow without overextending your budget.

Benefits

Designed for Unstable, Heavy Loads Ideal when rotating the pallet is not an option

Pre-Stretch Carriage Maximizes film yield and reduces material costs

Full-Color Control Panel Simple, intuitive setup for any load profile

Consistent Wrapping Quality Reduces product movement and damage during transport

Features

R-Connect R-Connect provides usage and performance data via the cloud. Meet Industry 4.0 demands with performance monitoring and optimization at your fingertips. R-Connect empowers you with actionable insight to promptly investigate alarms, adjust parameters, improve performance, reduce down

time.

3.5" Color Touch Screen With a 3.5" color LED screen and JOG dial programmable selector. Record up to 6 different programs.

PGS Carriage The PGS film carriage is a fixed 250% power pre-stretch gear. Force-to-load tension is controlled by a strain gauge, adjusted on the control panel. 150% and 200% power pre-stretch gears are optional.

Film Delivery System

- Fixed stretch: 250%
- Height sensing: Automatic photo eye
- Film threading: Patented S pattern
- Standard film width: 20"

Safety Features

- Safety bumper warning light
- Safety alarm
- CE Compliant, UL, CUL

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

Specifications

Production Speed	Up to 25 loads per hour
Wrap Arm Speed	11 RPM
Max Pallet Dimensions	48" x 48" x 94"
Max Pallet Weight	Unlimited
Power	120V, 18.2 amp, 60 Hz, 1 PH

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.