



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Robopac Rotoplat 508 DW & DW/C Semi-Auto Turntable Stretch Wrapper



At a Glance

- Contains doors, windows, and other similar products
- Max load weight DW: 220 lbs, DW/C: 330 lbs
- Optional Pluripac system applies foam or bubble wrap at the same time as stretch film

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Turntable Stretch Wrappers for Doors and Windows

The Robopac Rotoplat 508 DW and DW/C specialized turntable stretch wrapping machines are designed to properly secure doors, windows, and other similar products during storage and transport.

For wrapping single units or batches, Rotoplat 508 DW and DW/C stretch wrappers ensure doors and windows reach customers in perfect condition.

DW and DW/C Configurations

- DW: Manual product lock system for secure, hands-on load positioning
- DW/C: Idle roller conveyor for easier, more efficient product handling

Highlights

- 71" diameter turntable.
- Wraps items with a thickness of 1.5" to 14" thick, 30" to 70" wide, and 42" to 110" high.
- Adjustable brackets allow wrapping different sizes.
- PDS film carriage delivers 250% pre-stretch using fixed gears.
- Double stretch control switches the carriage to variable pre-stretch via a clutch positioned on the first roller.
- Containment force adjustable from color touchscreen control panel.
- Patented high-performance S wrap pattern with quick load system and load cell compensation and containment force.

- Foot pedal controls top platen, allows operator to hold door in place while lowering clamp to secure product.

Features

R-Connect R-Connect provides usage and performance data via the cloud. Meet Industry 4.0 demands with performance monitoring and optimization at your fingertips. R-Connect empowers you with actionable insight to promptly investigate alarms, adjust parameters, improve performance, reduce down time.

Color Touch Screen The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the multi-level control function.

PGS Carriage PDS carriage with dual pre-stretch rollers controlled via the control panel. Pre-stretch system stretch ratio adjustable from panel board up to 250%. Stretch Control activates the electromagnetic clutch positioned on the first roller making pre-stretch variable from 0%-250%.

Pluripac Option Provides More Protection The optional Pluripac delivery system applies foam or bubble wrap material at the same time as the stretch film. The Pluripac system provides additional padding for fragile wood and glass, making this equipment an extremely effective protective window and door wrapping machine.

Film Delivery System

- Standard pre-stretch: Variable 0 – 250%
- Containment force: Variable electronic
- Film carriage motor: ½ HP VAC
- Height sensing: Automatic via photocell
- Film threading: Patented S pattern
- Corner compensation: Load cell

Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

Specifications

Turntable Speed	5 - 12 RPM
Turntable Size	71" diameter
Max Pallet Load Dimensions	65"L x 98"H
Max Pallet Load Weight	DW: 220 lbs, DW/C: 330 lbs
Turntable Drive	1 hp VAC
Power	120V, 14 amp, 60 Hz, 1 PH

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.