



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Robopac Rotoplat 708 Semi-Auto Turntable Stretch Wrapper



At a Glance

- Up to 40 loads per hour
- Max load weight 4400 lbs
- Max load height: 110 inches
- Adjust containment force up to nine times per load

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Maximum Control. Minimal Waste. Ultimate Load Protection.

The Robopac Rotoplat 708 is engineered with patented features and smart automation to wrap any load with unmatched precision.

Equipped with Cube Technology and a 7-inch color touchscreen, the Rotoplat 708 makes complex wrapping simple. Its patented roll carriage and multi-level variable containment system can adjust containment force up to nine times per load, ensuring optimal film application for every product type and pallet load.

The Robopac Rotoplat 708 ensures every pallet is securely wrapped and ready to ship - while saving material, labor, and time.

Highlights

Cube Technology Reduce film usage by 30%–55%, and cut product damage by up to 40%.

7-Inch Touchscreen Interface User-friendly control with visual load programming.

Multi-Level Variable Containment Adjust wrap force at nine points to match load fragility and stability.

Patented Roll Carriage Confidently wrap any load with any film.

R-Connect Standard Includes 36-month cellular plan for remote diagnostics and performance tracking.

Features

R-Connect R-Connect provides usage and performance data via the cloud. Meet Industry 4.0 demands with performance monitoring and optimization at your fingertips. R-Connect empowers you with actionable insight to promptly investigate alarms, adjust parameters, improve performance, reduce down time.

Color Touch Screen The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the multi-level control function.

PVS Carriage Powered stretch system controlled by two motors. Stretch ratio adjustable from panel board from 150–400%. Force to the load controlled by patented electronic device and adjustable from panel board.

High Profile Version

- Ideal for concrete block and brick industry
- Easy loading with forklift truck
- Ideal for pallet load of bagged products with a high profile
- Allows product to fall onto the floor instead of under the turntable
- Complete pallet wrapping with high profile turntable that allows the carriage to move further down
- Heavy-duty design
- 5500 lb weight capacity

Stainless Steel Version Ideal for processing, wet or cold applications. The Robopac stainless steel Rotoplat 708 stretch wrapper is designed for industries requiring high hygiene like meat, poultry, fish, dairy, beverage and wherever high food safety is essential.

Film Delivery System

- Containment Force: Variable electronic
- Film Carriage Motor: ½ HP VAC
- Height Sensing: Automatic via photocell
- Film Threading: Patented S pattern
- Corner Compensation: Load cell

Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

Specifications

Production Speed	Up to 40 loads per hour
Turntable Speed	5 - 12 RPM
Turntable Size	65" diameter
Max Pallet Load Height	110"
Max Pallet Load Weight	4400 lbs
Turntable Drive	1 hp VAC
Power	120V, 14 amp, 60 Hz, 1 PH

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.