



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Robopac Rotoplat Stainless Steel 708 Semi-Auto Turntable Stretch Wrapper



At a Glance

- Fully stainless steel semi-automatic stretch wrapping machine
- Up to 40 loads per hour
- Max load weight 4400 lbs
- Max load height: 110 inches

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Stretch Wrapper Built to Withstand Harsh Conditions

The Robopac Stainless Steel Rotoplat 708 is a fully stainless steel semi-automatic stretch wrapping machine, ideal for wet, cold, or washdown environments. Built for food processing, cold storage, or pharmaceutical facilities. Not a stainless coating, this machine is fully stainless to prevent corrosion from standing water and harsh conditions.

Highlights

True Stainless Steel Construction Fully resistant to rust—no painted or coated components.

Ideal for Processing Facilities Handles wet, cold, or humid conditions without degrading.

Cube Technology Reduces film usage by 30%–55% and potential product damage by up to 40%.

Patented Roll Carriage Flexibly wraps any load with any film with precision.

Multi-Level Variable Containment Adjust containment force up to 9 times per load for maximum control.

Consistent, Reliable Wrapping Keeps loads secure while maintaining hygiene and safety standards.

Stainless Steel Components

Stainless Steel Film Roll Carriage The Robopac Rotoplat 708 features an S winding pattern roll carriage that provides 40% more film contact than the W winding pattern. An S winding pattern provides better

control of film through the roll carriage and fewer film breaks.

This innovative, dual-motor pre-stretch system provides the ability to pre-stretch film from 150% up to 400% using two independent, variable AC motors. Both pre-stretch and containment force are adjustable via the operator control panel. Robopac patented high-performance S-wrap pattern (with quick load system) and load cell corner compensation and containment force device give you total film control.

The Rotoplat 708 variable pre-stretch delivers the best film economy for all films and all loads. Six selectable wrap patterns allow you to optimize each of your load types, reduce damage, improve productivity and reduce film costs. 100% Stainless Steel Materials or plastic non-corrosive components used in design.

Stainless Steel Control Panel The high performance 7-inch color touch screen provides multi-level control.

Stainless Steel HD Turntable The Rotoplat 708 turntable is supported by 28 heavy duty casters and can handle loads up to 4,400 lbs. Weight capacity increases to 5,500 lbs by adding 16 casters. This can be done at order entry or added later in the field.

The heavy-duty 65-inch turntable is powered by a full 1 horse power AC motor. The oversize turntable safely and easily accommodates a 40" x 48" with no overhang.

Features

R-Connect R-Connect provides usage and performance data via the cloud. Meet Industry 4.0 demands with performance monitoring and optimization at your fingertips. R-Connect empowers you with actionable insight to promptly investigate alarms, adjust parameters, improve performance, reduce down time.

Color Touch Screen The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the multi-level control function.

PVS Carriage Powered stretch system controlled by two motors. Stretch ratio adjustable from panel board from 150-400%. Force to the load controlled by patented electronic device and adjustable from panel board.

High Profile Version

- Ideal for concrete block and brick industry
- Easy loading with forklift truck
- Ideal for pallet load of bagged products with a high profile
- Allows product to fall onto the floor instead of under the turntable
- Complete pallet wrapping with high profile turntable that allows the carriage to move further down
- Heavy-duty design
- 5500 lb weight capacity

Stainless Steel Version Ideal for processing, wet or cold applications. The Robopac stainless steel Rotoplat 708 stretch wrapper is designed for industries requiring high hygiene like meat, poultry, fish, dairy, beverage and wherever high food safety is essential.

Film Delivery System

- Containment Force: Variable electronic

- Film Carriage Motor: ½ HP VAC
- Height Sensing: Automatic via photocell
- Film Threading: Patented S pattern
- Corner Compensation: Load cell

Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.

Specifications

Production Speed	Up to 40 loads per hour
Turntable Speed	5 - 12 RPM
Turntable Size	65" diameter
Max Pallet Load Height	110"
Max Pallet Load Weight	4400 lbs
Turntable Drive	1 hp VAC
Power	120V, 14 amp, 60 Hz, 1 PH

Please [contact Pro Pac](#) or call 888-318-0083 for your stretch wrapping equipment.