



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Ossid 500im Intermittent Motion Leak Resistant Overwrapper

## At a Glance

- Uses 36% to 41% less film
- intermittent motion creates up to 40 trays per minute
- Produces tightly wrapped case-ready packages

Buy your [tray wrapping film](#) from us, and get a discount on this Ossid tray overwrapper!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



## Much Less Film at Steady Speeds

The Ossid 500im is a cost effective end seal overwrapper, producing tightly wrapped case-ready packages at speeds up to 40 trays per minute.

## Features & Benefits

- Uses 36% to 41% less film than standard overwrap packaging machines
- Consistent tightly wrapped packaging
- Leak resistant end seals
- Welded center seal allows for easy printing on both the top and bottom of packages
- Runs tray sizes from #2 to 10" x 15" including #9 and heights up to 5.25"
- Runs at speeds up to 40 packages per minute
- Creates leak resistant high or low profile case-ready packaging
- Gripper chain system consistently stretches shrink films to produce tightly wrapped packages
- Stores up to 50 tray programs for easy product changeover in less than two minutes
- Servo-driven technology and microprocessors reduce downtime and maintenance
- Open stainless steel frame
- Leak proof packaging equipment

## Options

- 500HWT Hot Water Tunnel provides hot water shrink to maximize package integrity.
- Water Recirculation System cools the machine with as little as one gallon of water per day, resulting in huge savings. Without this system, the 500-IM uses 1.5 gallons of water per minute.

Trimmed Center Seal trims excess film away, providing more visibility to printed graphics on the bottom of the package.

## Technical Specifications

Length: 146" (3,708mm)

Height: 52" (1,321mm)

Width: 49" (1245mm)

Electrical: 208/230 VAC, 30 amp, 3 phase

Please [contact Pro Pac](#) or call 888-318-0083 for your tray packaging equipment.