



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Starview AITS-1215 Automatic Film to Tray Sealer

At a Glance

- Automatic tray conveyor system and optional tray feeder to reduce labor
- Automatic film feed, seal & trim and scrap rewind for clear or random print film
- 1 open loading station
- Stainless steel wash down construction

Buy your [trays](#) from us, and get a discount on this Starview tray sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Protect Your Food Products with Modified Atmosphere Packaging (MAP)

Starview AITS tray sealers are designed and competitively priced for fresh counter packaging, with clear or printed film to a preformed tray for food manufacturing companies, catering, grocery stores, etc.

The AITS-1215 machines produce sealed packages without a modified atmosphere.

The AITS Series is ideal for medium production. This series machines can adapt to seal for a wide range of product tray sizes by simply changing the tooling.

These machines trim the film to the profile of the tray and automatically rewind the scrap web. The AITS Series sealers will provide years of dependable performance with a minimum of maintenance.

Advantages & Benefits

A wide range of standard and custom features available to match customer requirements.

Automatic tray conveyor system and optional tray feeder to reduce labor and increase machine production rates.

Uses quick-change anodized aluminum tooling.

Convenient touch panel controls for operator convenience, accessibility and process repeatability.

Automatic film feed, seal & trim and scrap rewind for clear or random print film.

Registered print film feed optional.

Stainless steel wash down construction to allow cleaning in a food handling environment.

Industry leading design, construction, features and customer support.

Standard Features

Programmable logic control (Omron).

- PLC complete with recipe memory for up to 10 programs for quick machine setup.

Main power/Heater Off/On switch.

Automatic film feeding.

Automatic scrap rewinding.

Operator safety platen guard.

Interchangeable aluminum sealing fixtures.

Double acting sealing press.

Pneumatic system for film sealing and cutting.

Temperature controller with PID control system and PT100 probe in order to ensure continuous control of the sealing plates temperature.

Trims film to tray profile with appropriate tooling.

In-feed conveyor.

Finished package unload conveyor, gravity type.

Air filter, regulator and gauge.

Casters.

Anodized aluminum/stainless steel construction for wash down.

Operational Specifications

Number of open load stations: 1

Maximum sealing area: 12.2" x 15.3"

Maximum tray depth: 3.9"

Registered film: Optional

Maximum film width: 18.8"

Maximum film roll diameter: 9.4"

Average cycle speed: 1 to 15 cpm

Technical Specifications

Electrical: 208-240 Volts / 3 PH / 20 Amps

Actuator type: Pneumatic

Heating system: Temperature controlled interchangeable tooling

Air consumption per cycle: 100 psi

Approximate dimensions: 78"D x 33"W x 61"H

In-feed conveyor length: 40.3"

Out-feed conveyor length: 20"

Working Height: 37"

Approximate weight: 950 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your tray packaging equipment.