



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Starview MRTS-1418 Manual Rotary Tray Sealer



At a Glance

- Efficient two-station design
- Color touch screen HMI
- Automatic film feed, seal & trim and scrap rewind
- Stainless steel wash down construction
- MRTS/MAP-1418 model available with modified atmosphere packaging

Buy your [tray lidding film](#) from us, and get a discount on this Starview tray sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Quickly Package Your Food in This Low-Cost Tray Sealer

Starview MRTS-1418 tray sealing machines are designed and competitively priced for fresh counter packaging, typically a clear or printed film to a preformed tray for food manufacturing companies, catering, grocery stores, delicatessens, etc.

The MRTS Series is ideal for low to medium production. These tray sealing machines can adapt to seal for a wide range of product tray sizes by simply changing the tooling.

Starview MRTS tray sealers trim the film to the profile of the tray and automatically rewind the scrap web.

These tray sealers will provide years of dependable performance with a minimum of maintenance.

Advantages & Benefits

A wide range of standard and custom features available to match customer requirements.

Uses quick-change anodized aluminum tooling.

Efficient two-station design makes the MRTS Series ideal for medium volume production and work-cell manufacturing. Allows operators to load and unload trays in one station while the second station is being sealed.

Color touch screen HMI for the ultimate in operator convenience, accessibility and process repeatability.

Automatic film feed, seal & trim and scrap rewind for clear or random print film. Registered print film feed optional.

Stainless steel wash down construction to allow cleaning in a food handling environment.

Industry leading design, construction, features and customer support.

Standard Features

Programmable logic control (Omron).

- Intelligent system that allows changes or upgrades from a Starview provided memory card.
- Ethernet connection to PLC and HMI allows remote access by customer from PC, laptop, smartphones and tablet devices to HMI screens and PLC functions, and by Starview for program changes, diagnosis or updates when internet connected. Optional Wi-Fi connection available.

Color HMI includes:

- Time and date displayed on all screen pages.
- System monitoring page. Heating, batch counter and job recipe displayed at a glance.
- Full Job Recipe storage with memory for up to 100 different recipes.
- History page with last 200 cycles stored and displayed with time and date stamp.
- Sealing Timer.
- Digital temperature controller on screen display in degrees Fahrenheit or Celsius with alarms.
- Manual / Auto mode.
- Complete manual control of all individual functions for set up.
- Machine diagnostics with difficulty location.
- On-screen system errors for troubleshooting.
- Last 7-days alarms stored and displayed with time and date stamp.

Main power/Heater Off/On switch.

Emergency Stop button.

Automatic film feeding.

Optional printed and registered film feeder.

Automatic scrap rewinding.

Operator safety platen guard.

Interchangeable aluminum sealing fixtures.

Quick change tooling feature.

Pneumatic system for film sealing and cutting.

Trims film to tray profile with appropriate tooling.

Air filter, regulator and gauge.

Casters.

Anodized aluminum/stainless steel construction for wash down.

Operational Specifications

Maximum sealing area: 14" x 18"

Number of open load stations: 1

Profile film trim: Standard

Maximum tray dimensions: 14" x 18"

Maximum tray depth: 4.0"

Registered film: Optional

Maximum film width: 16.5"

Maximum film roll diameter: 9.5"

Average cycle speed: 1 to 6 cpm

Technical Specifications

Electrical: 208-230 Volts / 3 PH / 20 Amps

Heating system: Temperature controlled interchangeable tooling

Actuator type: Pneumatic

Supplied air requirement: 100 psi

Vacuum pump installed: N/A, Standard with MRTS/MAP-1418

Approximate dimensions: 41"D x 40"W x 56"H

Working height: 37"

Approximate weight: 850 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your tray packaging equipment.