



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Hayssen Ultima SVJ Sanitary VFFS Bagging System



At a Glance

- Open channel frame
- Sloped surfaces
- Servo-driven VFFS bagging system
- Heavy-duty jaw assembly
- Allen-Bradley PV1000 color touch-screen operator interface

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

The Hayssen Sanitary Frame Ultima SV is suited for environments where sanitation is a must. The Ultima SV has a long-standing reputation as a solid, durable member of the BWFS family of vertical form fill seal (VFFS) machines.

The Ultima SVJ's servo-driven system features off-the-shelf Allen-Bradley controls. Sealing systems for laminate and polyethylene packaging materials can be customized to meet your application requirements. Higher sanitation features are available.

Features & Benefits

Open channel frame

Sloped surfaces

High speed servo-driven jaws

User-friendly, upgraded Allen-Bradley control system with color touch screen operator interface

Heavy-duty jaw assembly houses a cushion for shock and noise abatement

Servo driven self-centering pull belts

More dwell time for better looking seals and increased packaging speeds using independent stager / cooler

Patented measure, form, pull film advance concept

Open frame for ease of access

Production Rate

Up to 120 ppm

Package Range

Minimum Width: 2 1/8" (54mm)

Minimum Length: 3" (76mm)

Maximum Width: 8" to 18" (203mm to 457mm) depending on frame size

Maximum Length: 8" to 28" (203mm to 711mm) depending on frame size

Variety of Feed Systems

Scales

Augers

Volumetrics and pumps

Options

Stainless steel construction

Integrated zipper applicator

Various hole punches

Tear notches

Code daters

Gas flushing

Static eliminators

Tucking devices

Power and Air Requirements

Power: 230/460 vac, single phase, 50/60 hz, 30 amp

Air: 2.5 scfm at 65 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your vertical form fill seal bagging equipment.